

APPENDIX A

AVIATION GASOLINE CONVERSION TABLE
CONVERSION FROM MOTOR METHOD RATINGS
TO CORRESPONDING AVIATION METHOD RATINGS^{a/}

Motor Octane Number	0.0	0.2	0.4	0.6	0.8
75	73.59	73.81	74.04	74.27	74.49
76	74.72	74.95	75.17	75.40	75.63
77	75.85	75.08	76.30	76.53	76.75
78	76.98	77.20	77.43	77.65	77.88
79	78.10	78.33	78.55	78.77	79.00
80	79.22	79.44	79.67	79.89	80.11
81	80.33	80.55	80.78	81.00	81.22
82	81.44	81.66	81.88	82.10	82.32
83	82.55	82.77	82.99	83.21	83.43
84	83.65	83.86	84.08	84.30	84.52
85	84.74	84.96	85.18	85.40	85.61
86	85.83	86.05	86.27	86.48	86.70
87	86.92	87.13	87.35	87.57	87.78
88	88.00	88.22	88.43	88.65	88.86
89	89.08	89.29	89.51	89.72	89.94
90	90.15	90.37	90.58	90.79	91.01
91	91.22	91.43	91.65	91.86	92.07
92	92.29	92.50	92.71	92.92	93.13
93	93.35	93.56	93.77	93.98	94.19
94	94.40	94.61	94.82	95.04	95.25
95	95.46	95.67	95.88	96.09	96.29
96	96.50	96.71	96.92	97.13	97.34
97	97.55	97.76	97.96	98.17	98.38
98	98.57	98.74	98.91	99.08	99.26
99	99.43	99.60	99.78	99.95	100.44
100	101.07	101.60	102.14	102.67	103.21
101	103.74	104.27	104.81	105.34	105.88
102	106.41	106.94	107.48	108.01	108.55
103	109.08	109.61	110.51	110.68	111.22
104	111.75	112.28	112.82	113.35	113.89
105	114.42	114.95	115.49	116.02	116.56
106	117.09	117.62	118.16	118.69	119.23
107	119.76	120.29	120.83	121.36	121.90
108	122.43	122.96	123.50	124.03	124.57
109	125.10	125.63	126.17	127.70	127.24
110	127.77	128.30	128.84	129.37	129.91

Equations: Correlation equations—reference report "Aviation Gasoline Antiknock Quality by ASTM Methods D 614 and D 357," June 21, 1966, Fig. 4.

Less than 93 motor performance number (97.89 motor octane number).

Aviation performance number = $-5.6 + 1.08$ (motor performance number).

Greater than 93 motor performance number

Aviation performance number = $12.07 + 0.89$ (motor performance number).

Conversion equations—

Below 100: performance number = $2800/(128 - \text{octane number})$

Above 100: performance number = $100 + (\text{octane number} - 100)^3$

^{a/} Octane numbers in *italics*, performance numbers in "regular" type.