

restrictions given in subsections (1) and (4). In all cases, the entire flare shall fall within the right of way.

(3) **ANGULAR PLACEMENT OF DRIVE.** The angle between the centerline of the driveway and the curb line shall be not less than 45 degrees.

(4) **ISLAND AREAS.** (a) When sidewalk is adjacent to curb, an island of a minimum length of 6 feet, measured along the curb line, shall be placed between each entrance to a state highway. The curb shall be left intact for this length.

(b) When sidewalk is remote from curb, an island of a minimum length of 10 feet measured along the right-of-way line shall be maintained between each entrance to a state highway. All flares shall be tangent to the curb line.

(c) A curb length of not less than 3 feet shall be left undisturbed adjacent to each property line to serve as an island area should the adjoining property owner request a permit for an entrance.

**Hy 31.07 Noncommercial-urban.** On urban type highway cross section, driveways serving residence property shall conform to the following:

(1) **WIDTH OF DRIVE.** No noncommercial driveway or combination of driveways shall have a width greater than 24 feet measured at right angles to the centerline of the driveway, except as increased by permissible radii.

(2) **RETURN RADII.** The radius of the return connecting the line of face of curb of the highway and the edge of driveway shall not exceed 10 feet. In all cases the entire flare shall fall within the right of way.

(3) **ANGULAR PLACEMENT.** The centerline of the driveway may be either parallel to the property line of the lot for which access is requested, or at right angles to the curb line.