NR 25

Chapter NR 253

COPPER FORMING

NR 253.01 NR 253.02 NR 253.03 NR 253.04 NR 253.05	Purpose Applicability General definitions Monitoring and reporting re- quirements Compliance dates	NR 253.12	Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable
	- The copper forming Applicability; description of the copper forming subcategory Effluent limitations represent-	NR 253.13 NR 253.14 NR 253.15	
	ing the degree of effluent re- duction attainable by the ap- plication of the best practicable control technol- ony currently available	Subchapter I forming subc [Reserved]	I - The beryllium copper ategory

NR 253.01 Purpose. The purpose of this chapter is to establish effluent limitations, standards of performance, and pretreatment standards for discharges of process wastes from the copper forming point source category and its subcategories.

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89

NR 253.02 Applicability. This chapter applies to discharges resulting from hot rolling, cold rolling, drawing, extrusion, and forging of copper and copper alloys and the associated ancillary operations. This chapter does not apply to the forming of precious metals, which is regulated by 40 C.F.R. 471, or the casting of copper or copper alloys, which is regulated by ch. NR 256.

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89

NR 253.03 General definitions. The following definitions are applicable to the terms used in this chapter. Definitions of other terms and abbreviations are set forth in ss. NR 205.03, 205.04, and 211.03.

- (1) "Alkaline cleaning bath" means a bath consisting of an alkaline cleaning solution through which a workpiece is processed.
- (2) "Alkaline cleaning rinse" means a rinse following an alkaline cleaning bath through which a workpiece is processed. A rinse consisting of a series of rinse tanks is considered as a single rinse.
- (3) "Alkaline cleaning rinse for forged parts" means a rinse following an alkaline cleaning bath through which a forged part is processed. A rinse consisting of a series of rinse tanks is considered as a single rinse.
- (4) "Ancillary operation" means an operation, such as surface and heat treatment, hydrotesting, sawing, and surface coating, associated with a primary forming operation.
- (5) "Annealing with oil" means the use of oil to quench a workpiece as it passes from an annealing furnace.

NR 253

- (6) "Annealing with water" means the use of a water spray or bath, of which water is the major constituent, to quench a workpiece as it passes from an annealing furnace.
- (7) "Beryllium copper alloy" means any copper alloy that is alloyed to contain 0.10% or greater beryllium.
- (8) "Cold rolling" means the process of rolling a workpiece below the recrystallization temperature of the copper or copper alloy.
- (9) "Drawing" means pulling the workpiece through a die or succession of dies to reduce the diameter or alter its shape.
- (10) "Existing source" means any point source, except for a new source as defined in sub. (16), from which pollutants may be discharged either into waters of the state or into a publicly owned treatment works.
- (11) "Extrusion" means the application of pressure to a copper workpiece, forcing the copper to flow through a die orifice.
- (12) "Extrusion heat treatment" means the spray application of water to a workpiece for the purpose of heat treatment immediately following extrusion.
- (13) "Hot rolling" means the process of rolling a workpiece above the recrystallization temperature of the copper or copper alloy.
- (14) "Heat treatment" means the application of heat to or the removal of heat from a workpiece to change the physical properties of the metal.
- (15) "Miscellaneous waste stream" means hydrotesting, sawing, surface milling, and maintenance wastestreams when they are related to the forming of copper.
- (16) "New source", as defined for new source performance standards and pretreatment standards for new sources, means any point source for which construction commenced after November 12, 1982 and from which pollutants are or may be discharged directly to the waters of the state or to a publicly owned treatment works.
- (17) "Off kilogram" and "off pound" mean the mass of copper or copper alloy removed from a forming or ancillary operation at the end of a process cycle for transfer to a different machine or process.
- (18) "Pickling bath" means a chemical bath, other than an alkaline cleaning bath, through which a workpiece is processed.
- (19) "Pickling fume scrubber" means an air pollution control device which removes particulates and fumes from air above a pickling bath by entraining the pollutants in water.
- (20) "Pickling rinse" means a rinse, other than an alkaline cleaning rinse, through which a workpiece is processed. A rinse consisting of a series of rinse tanks is considered as a single rinse.
- (21) "Pickling rinse for forged parts" means a rinse, other than an alkaline cleaning rinse, through which forged parts are processed. A rinse consisting of a series of tanks is considered as a single rinse.

- (22) "Precious metals" means gold, platinum, palladium, silver, and their alloys when the alloy contains 30 percent or greater percent by weight of precious metals.
- (23) "Primary forming operation" means hot rolling, cold rolling, drawing, extrusion, and forging of copper and copper alloys.
- (24) "Rolling" means reducing the thickness or diameter of a workpiece by passing it between rollers.
- (25) "Solution heat treatment" means introducing a workpiece into a quench bath for purposes of heat treatment.
- (26) "Spent lubricant" means water or an oil and water mixture which has been used in forming operations to reduce friction, heat, and wear and which is discharged.
- (27) "Surface coating" means the process of coating a copper workpiece, as well as the associated surface washing and flattening.
- (28) "Total toxic organics" and "TTO" mean the sum of the masses or concentrations of each of the following organic compounds which is found at a concentration greater than 0.010 mg/1:

anthracene benzene chloroform 2,6-dinitrotoluene ethylbenzene methylene chloride napthalene N-nitrosodiphenylamine phenanthrene toluene 1,1,1-trichloroethane trichlorethylene.

(29) "Tumbling or burnishing" means polishing, deburring, removing sharp corners, and generally smoothing parts for both cosmetic and functional purposes and washing the finished parts and cleaning the abrasive media.

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89

- NR 253.04 Monitoring and reporting requirements. The following special monitoring and reporting requirements apply to all facilities subject to this chapter:
- (1) The "monthly average" regulatory values shall be the basis for the monthly average discharge in direct discharge permits and for pretreatment standards. Compliance with the monthly discharge limit is required regardless of the number of samples analyzed and averaged.
- (2) As an alternate monitoring procedure for TTO, indirect dischargers may monitor for oil and grease and meet the alternate monitoring standards for oil and grease established for PSES and PSNS. Any indirect discharger meeting the alternate monitoring standards shall be considered to meet the TTO standard.

NR 253.05 Compliance dates. (1) Any existing source subject to this chapter which discharges to waters of the state shall achieve:

- (a) the effluent limitations representing BPT by July 1, 1977; and
- (b) the effluent limitations representing BAT by July 1, 1984.
- (2) Any new source subject to this chapter which discharges to waters of the state shall achieve NSPS at the commencement of discharge.
- (3) Any existing source subject to this chapter which introduces process wastewater pollutants into a POTW shall achieve PSES by August 15, 1986:
- (4) Any new source subject to this chapter which introduces process wastewater pollutants into a POTW shall achieve PSNS at the commencement of discharge.

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89

Subchapter I — The Copper Forming Subcategory

NR 253.10 Applicability; description of the copper forming subcategory. This subchapter applies to the discharge of pollutants to waters of the state and the introduction of pollutants into POTWs from the forming of copper and copper alloys except beryllium copper alloys.

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89

NR 253.11 Effluent limitations representing the degree of effluent reduction attainable by the application of the best practicable control technology currently available. Except as provided in 40 C.F.R. ss. 125.30 to 125.32, any existing source subject to this subchapter shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of BPT:

Table 1 Hot Rolling Spent Lubricant

BPT Effluent Limitations				
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy hot rolled			
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0.045 0.195 0.015 0.197 0.150 2.060 4.223 (1)	0.018 0.103 0.013 0.130 0.062 1.236 2.008 (1)		

⁽¹⁾ Within the range of 7.5 to 10.0 at all times

Table 2 Cold Rolling Spent Lubricant

BPT Effluent Limitations				
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	off-pounds) of c	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy cold rolled		
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0.166 0.720 0.056 0.727 0.553 7.580 15.539 (1)	0.068 0.379 0.049 0.481 0.231 4.548 7.390 (1)		

Table 3
Drawing Spent Lubricant(1)

Drawing Spent Lubricant(1)				
BPT Effluent Limitations				
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy drawn				
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0.037 0.161 0.012 0.163 0.124 1.700 3.485 (2)	0.015 0.085 0.011 0.107 0.051 1.020 1.657 (2)		

⁽¹⁾ These effluent limitations are applicable only to those plants which actually discharge the drawing spent lubricant waste stream at the copper forming site. If these wastewaters are hauled off-site for disposal or are otherwise not discharged at the copper forming site, these limitations are neither applicable nor allowable.

Table 4 Solution Heat Treatment

BPT Effluent Limitations				
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated			
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	1.118 4.827 0.381 4.878 3.709 50.820 104.181 (1)	0.457 2.541 0.330 3.227 1.550 30.492 49.549 (1)		

Table 5 Extrusion Heat Treatment

BPT	Γ Effluent Limitations		
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	off-pounds) of o	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0.00088 0.003 0.0003 0.003 0.002 0.040 0.082 (1)	0.00036 0.002 0.00026 0.002 0.001 0.024 0.039 (1)	

Table 6 Annealing With Water

BPT Effluent Limitations				
	Maximum for any 1 day	Maximum for monthly average		
mg/off-kg (pounds per 1,000,000 Pollutant or off-pounds) of copper or copper pollutant property alloy annealed with water				
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	2.439 10.767 0.850 10.880 8.273 113.340 232.347 (1)	1.020 5.667 0.736 7.197 3.456 68.004 110.506 (1)		

Table 7 Annealing With Oil

BPT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper ollutant property alloy annealed with oil			
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0 0 0 0 0 0 0 0 0 0 0 0	0 0 0 0 0 0 0 0 0 0 0	

Table 8 Alkaline Cleaning Rinse

BPT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (poun off-pounds) of co alloy alkaline cle	opper or copper	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	1.854 8.006 0.632 8.090 6.152 84.280 172.774 (1)	0.758 4.214 0.547 5.351 2.570 50.568 82.173 (1)	

⁽¹⁾ Within the range of 7.5 to 10.0 at all times

Table 9
Alkaline Cleaning Rinse For Forged Parts

BPT Effluent Limitations				
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy forged parts alkaline cleaned			
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	5.562 24.019 1.896 24.272 18.457 252.840 518.322 (1)	2.275 12.642 1.643 16.055 7.711 151.704 246.519 (1)		

⁽¹⁾ Within the range of 7.5 to 10.0 at all times

Table 10 Alkaline Cleaning Bath

BPT Effluent Limitations				
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	off-pounds) of c	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned		
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0.020 0.089 0.0070 0.089 0.068 0.93 1.91 (1)	0.0084 0.046 0.0060 0.059 0.028 0.56 0.91 (1)		

Table 11 Pickling Rinse

BPT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property		nds per 1,000,000 opper or copper	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	1.593 6.881 0.543 6.954 5.288 72.440 148.502 (1)	0.651 3.622 0.470 4.599 2.209 43.464 70.629 (1)	

Table 12 Pickling Rinse For Forged Parts

BPT Effluent Limitations		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy forged parts pickled	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	1.723 7.444 0.587 7.522 5.720 78.360 160.638 (1)	0.705 3.918 0.509 4.975 2.389 47.016 76.401 (1)

⁽¹⁾ Within the range of 7.5 to 10.0 at all times

Table 13 Pickling Bath

I leating Dath			
BPT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled		
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0.051 0.220 0.017 0.222 0.169 2.320 4.756 (1)	0.020 0.116 0.015 0.147 0.070 1.392 2.262 (1)	

⁽¹⁾ Within the range of 7.5 to 10.0 at all times

NR 253

Table 14 Pickling Fume Scrubber

BPT Effluent Limitations		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0.275 1.189 0.093 1.201 0.913 12.520 25.666 (1)	0.112 0.626 0.081 0.795 0.381 7.512 12.207 (1)

⁽¹⁾ Within the range of 7.5 to 10.0 at all times

Table 15 Tumbling or Burnishing

BPT Effluent Limitations		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy tumbled or burnished	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0.256 1.107 0.087 1.119 0.851 11.660 23.903 (1)	0.104 0.583 0.075 0.740 0.355 6.996 11.368 (1)

⁽¹⁾ Within the range of 7.5 to 10.0 at all times

Table 16 Surface Coating

BPT Effluent Limitations			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy surface coated		
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0.326 1.411 0.111 1.426 1.084 14.680 30.463 (1)	0.133 0.743 0.096 0.943 0.453 8.916 14.488 (1)	

Table 17 Miscellaneous Waste Streams

BPT Effluent Limitations		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy formed	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0.009 0.041 0.003 0.041 0.031 0.436 0.893 (1)	0.003 0.021 0.002 0.027 0.013 0.261 0.425 (1)

(1) Within the range of 7.5 to 10.0 at all times

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89

NR 253

NR 253.12 Effluent limitations representing the degree of effluent reduction attainable by the application of the best available technology economically achievable. Except as provided in 40 C.F.R. ss. 125.30 to 125.32, any existing source subject to this subchapter shall achieve the following effluent limitations representing the degree of effluent reduction attainable by the application of BAT:

Table 18 Hot Rolling Spent Lubricant

BAT Effluent Limitations		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy hot rolled	
Chromium Copper Lead Nickel Zinc	0.045 0.195 0.015 0.197 0.150	0.018 0.103 0.013 0.130 0.062

Table 19 Cold Rolling Spent Lubricant

BAT Effluent Limitations		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy cold rolled	
Chromium Copper Lead Nickel Zinc	0.166 0.720 0.056 0.727 0.553	0.068 0.379 0.049 0.481 0.231

Table 20 Drawing Spent Lubricant

BAT Effluent Limitations		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy drawn	
Chromium Copper Lead Nickel Zinc	$\begin{array}{ccc} 0.037 & 0.015 \\ 0.161 & 0.085 \\ 0.012 & 0.011 \\ 0.163 & 0.107 \\ 0.124 & 0.051 \end{array}$	

Table 21 Solution Heat Treatment

BAT Effluent Limitations		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated	
Chromium Copper Lead Nickel Zinc	0.284 1.227 0.096 1.240 0.943	0.116 0.646 0.083 0.820 0.394

Table 22 Extrusion Heat Treatment

BAT Effluent Limitations		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated	
Chromium Copper Lead Nickel Zinc	0.00088 0.003 0.0003 0.003 0.002	0.00036 0.0020 0.00026 0.002 0.001

Table 23 Annealing With Water

BAT Effluent Limitations		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy annealed with water	
Chromium Copper Lead Nickel Zinc	0.545 2.356 0.186 2.380 1.810	0.223 1.240 0.161 1.574 0.756

Table 24 Annealing With Oil

BAT	Effluent Limitations	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy annealed with oil	
Chromium Copper Lead Nickel Zinc	0 0 0 0 0	0 0 0 0

Table 25 Alkaline Cleaning Rinse

BAT	Effluent Limitations	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned	
Chromium Copper Lead Nickel Zinc	1.854 8.006 0.632 8.090 6.152	0.758 4.214 0.547 5.351 2.570

Table 26 Alkaline Cleaning Rinse For Forged Parts

BAT Effluent Limitations		
		Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,00 off-pounds) of copper or coppe alloy forged parts alkaline clea	
Chromium Copper Lead Nickel Zinc	5.562 24.019 1.896 24.272 18.457	2.275 12.642 1.643 16.055 7.711

Table 27 Alkaline Cleaning Bath

BAT	Effluent Limitations	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,00 off-pounds) of copper or coppe alloy alkaline cleaned	
Chromium Copper Lead Nickel Zinc	0.020 0.088 0.0070 0.089 0.068	0.0084 0.046 0.0060 0.059 0.028

Table 28 Pickling Rinse

BAT	Effluent Limitations	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,00 off-pounds) of copper or copper alloy pickled	
Chromium Copper Lead Nickel Zinc	0.574 2.481 0.195 2.507 1.906	0.235 1.306 0.169 1.658 0.796

Table 29		
Pickling Rinse For Forged Parts		

BAT	E 囲uent Limitations	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy forged parts pickled	
Chromium Copper Lead Nickel Zinc	1.723 7.444 0.587 7.522 5.720	0.705 3.918 0.509 4.975 2.389

Table 30 Pickling Bath

BAT Effluent Limitations		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled	
Chromium Copper Lead Nickel Zinc	0.051 0.220 0.017 0.222 0.169	0.020 0.116 0.015 0.147 0.070

Table 31 Pickling Fume Scrubber

BAT	Effluent Limitations	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled	
Chromium Copper Lead Nickel Zinc	0.275 1.189 0.093 1.201 0.913	0.112 0.626 0.081 0.795 0.381

Table 32 Tumbling or Burnishing

BAT	Effluent Limitations	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy tumbled or burnished	
Chromium Copper Lead Nickel Zinc	$\begin{array}{ccc} 0.256 & 0.104 \\ 1.107 & 0.583 \\ 0.087 & 0.075 \\ 1.119 & 0.740 \\ 0.851 & 0.355 \end{array}$	

Table 33 Surface Coating

BAT	Effluent Limitations	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy surface coated	
Chromium Copper Lead Nickel Zinc	0.326 1.411 0.111 1.426 1.084	0.133 0.743 0.096 0.943 0.453

DEPARTMENT OF NATURAL RESOURCES

216-37

NR 253

Table 34 Miscellaneous Waste Streams

BAT Effluent Limitations		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,00 off-pounds) of copper or copper alloy formed	
Chromium Copper Lead Nickel Zinc	0.009 0.041 0.003 0.041 0.031	0.003 0.021 0.002 0.027 0.013

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89

NR 253.13 New source performance standards. The discharge of process wastewater pollutants from any new source subject to this subchapter may not exceed the following NSPS:

Table 35 Hot Rolling Spent Lubricant

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy hot rolled	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0.038 0.131 0.010 0.056 0.105 1.030 1.545 (1)	0.015 0.062 0.0092 0.038 0.043 1.030 1.236 (1)

Table 36 Cold Rolling Spent Lubricant

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy cold rolled	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0.140 0.485 0.037 0.208 0.386 3.790 5.685 (1)	0.056 0.231 0.034 0.140 0.159 3.790 4.548 (1)

(1) Within the range of 7.5 to 10.0 at all times

Table 37 Drawing Spent Lubricant

NSPS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy drawn	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	$\begin{array}{cccc} 0.031 & 0.012 \\ 0.108 & 0.051 \\ 0.0085 & 0.0076 \\ 0.046 & 0.031 \\ 0.086 & 0.035 \\ 0.85 & 0.85 \\ 1.275 & 1.020 \\ (1) & (1) \end{array}$	

Table 38 Solution Heat Treatment

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	$\begin{array}{cccc} 0.239 & 0.096 \\ 0.826 & 0.394 \\ 0.064 & 0.058 \\ 0.355 & 0.239 \\ 0.658 & 0.271 \\ 6.460 & 6.460 \\ 9.690 & 7.752 \\ (1) & (1) \end{array}$	

Table 39 Extrusion Heat Treatment

NSPS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0.00074 0.0020 0.00020 0.0010 0.0020 0.020 0.030 (1)	0.00030 0.0010 0.00018 0.00074 0.00084 0.020 0.024 (1)

Table 40 Annealing With Water

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy annealed with water	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0.458 1.587 0.124 0.682 1.264 12.400 18.600 (1)	0.186 0.756 0.111 0.458 0.520 12.400 14.880 (1)

Table 41 Annealing With Oil

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy annealed with oil	
Chromium	0	0
Copper	Ō	Ō
Lead	0	0
Nickel	0	0
Zinc	0	0
Oil and grease	0	0
TSS	0	0
pH	(1)	(1)

Table 42 Alkaline Cleaning Rinse

NSPS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	1.559 5.393 0.421 2.317 4.298 42.140 63.210 (1)	0.632 2.570 0.379 1.559 1.769 42.140 50.568 (1)

Table 43 Alkaline Cleaning Rinse For Forged Parts

NSPS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,00 off-pounds) of copper or copper alloy alkaline cleaned	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	4.677 16.181 1.264 6.953 12.894 126.420 189.630 (1)	1.896 7.711 1.137 4.677 5.309 126.420 151.704

Table 44 Alkaline Cleaning Bath

	NSPS	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	$\begin{array}{cccc} 0.017 & 0.0070 \\ 0.059 & 0.028 \\ 0.0046 & 0.0042 \\ 0.025 & 0.017 \\ 0.047 & 0.019 \\ 0.46 & 0.46 \\ 0.70 & 0.56 \\ (1) & (1) \end{array}$	

(1) Within the range of 7.5 to 10.0 at all times

Table 45 Pickling Rinse

NSPS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0.216 0.748 0.058 0.321 0.596 5.850 8.775 (1)	0.087 0.356 0.052 0.216 0.245 5.850 7.020 (1)

Table 46 Pickling Rinse For Forged Parts

NSPS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy forged parts pickled	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	$\begin{array}{cccc} 0.649 & 0.263 \\ 2.246 & 1.070 \\ 0.175 & 0.157 \\ 0.965 & 0.649 \\ 1.790 & 0.737 \\ 17.550 & 17.550 \\ 26.325 & 21.060 \\ (1) & (1) \end{array}$	

Table 47 Pickling Bath

	=	
NSPS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0.042 0.148 0.011 0.063 0.118 1.160 1.740 (1)	0.017 0.070 0.010 0.042 0.048 1.160 1.392 (1)

Table 48 Pickling Fume Scrubber

NSPS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0.231 0.801 0.062 0.344 0.638 6.260 9.390 (1)	0.093 0.381 0.056 0.231 0.262 6.260 7.512

⁽¹⁾ Within the range of 7.5 to 10.0 at all times

Table 49 Tumbling or Burnishing

NSPS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy tumbled or burnished	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	0.215 0.746 0.058 0.320 0.594 5.830 8.745 (1)	0.087 0.355 0.052 0.215 0.244 5.830 6.996 (1)

⁽¹⁾ Within the range of 7.5 to 10.0 at all times

Table 50 Surface Coating

NSPS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy surface coated	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	$egin{array}{c} 0.274 \\ 0.951 \\ 0.074 \\ 0.408 \\ 0.757 \\ 7.430 \\ 11.145 \\ (1) \\ \end{array}$	0.111 0.453 0.066 0.274 0.312 7.430 8.916 (1)

Table 51 Miscellaneous Waste Streams

NSPS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy formed	
Chromium Copper Lead Nickel Zinc Oil and grease TSS pH	$\begin{array}{cccc} 0.008 & 0.003 \\ 0.027 & 0.013 \\ 0.0021 & 0.0019 \\ 0.011 & 0.008 \\ 0.022 & 0.009 \\ 0.218 & 0.218 \\ 0.327 & 0.261 \\ (1) & (1) \end{array}$	

(1) Within the range of 7.5 to 10.0 at all times

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89

NR 253.14 Pretreatment standards for existing sources. Except as provided in ss. NR 211.13 and 211.14, any existing source subject to this subchapter which introduces pollutants into a POTW shall comply with ch. NR 211 and achieve the following PSES:

Table 52 Hot Rolling Spent Lubricant

PSES		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy hot rolled	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	$\begin{array}{cccc} 0.045 & 0.018 \\ 0.195 & 0.103 \\ 0.015 & 0.013 \\ 0.197 & 0.130 \\ 0.150 & 0.062 \\ 0.066 & 0.035 \\ 2.060 & 1.236 \\ \end{array}$	

⁽¹⁾ For alternate monitoring

Table 53 Cold Rolling Spent Lubricant

PSES		
Maximum for any 1 day		Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy cold rolled	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	$\begin{array}{cccc} 0.166 & 0.068 \\ 0.720 & 0.379 \\ 0.056 & 0.049 \\ 0.727 & 0.481 \\ 0.553 & 0.231 \\ 0.246 & 0.128 \\ 7.580 & 4.548 \end{array}$	

⁽¹⁾ For alternate monitoring

Table 54
Drawing Spent Lubricant(1)

PSES Maximum for Maximum for monthly average		
Chromium Copper Lead Nickel Zinc TTO Oil and grease(2)	$\begin{array}{cccc} 0.037 & 0.015 \\ 0.161 & 0.085 \\ 0.012 & 0.011 \\ 0.163 & 0.107 \\ 0.124 & 0.051 \\ 0.055 & 0.028 \\ 1.700 & 1.020 \\ \end{array}$	

(1) These standards are applicable only to those plants which actually discharge the drawing spent lubricant waste stream at the copper forming site. If these wastewaters are hauled off-site for disposal or are otherwise not discharged at the copper forming site, these standards are neither applicable or allowable.

(2) For alternate monitoring

Table 55 Solution Heat Treatment

PSES		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated	
Chromium Copper Lead Nickel Zinc TTO Oil and grease	$\begin{array}{cccc} 0.284 & 0.116 \\ 1.227 & 0.646 \\ 0.096 & 0.083 \\ 1.240 & 0.820 \\ 0.943 & 0.394 \\ 0.419 & 0.219 \\ 12.920 & 7.752 \\ \end{array}$	

Table 56 Extrusion Heat Treatment

PSES		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,00 off-pounds) of copper or coppe alloy heat treated	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	0.00088 0.0030 0.00030 0.0030 0.0020 0.0010 0.040	0.00036 0.0020 0.00026 0.0020 0.0010 0.00068 0.024

⁽¹⁾ For alternate monitoring

Table 57 Annealing With Water

PSES		
any 1 day for m		Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy annealed with water	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	0.545 2.356 0.186 2.380 1.810 0.806 24.800	0.223 1.240 0.161 1.574 0.756 0.421 14.880

⁽¹⁾ For alternate monitoring

Table 58 Annealing With Oil

	PSES	
	Maximum fo any 1 day	or Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,00 off-pounds) of copper or copper alloy annealed with oil	
Chromium	0 0	
Copper	0	0
Leâd	0	0
Nickel	0 0	
Zinc	0	Ö
TTO	0	Ō
Oil and grease(1)	0	ñ

Table 59 Alkaline Cleaning Rinse

PSES		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	$\begin{array}{cccc} 1.854 & 0.758 \\ 8.006 & 4.214 \\ 0.632 & 0.547 \\ 8.090 & 5.351 \\ 6.152 & 2.570 \\ 2.739 & 1.432 \\ 84.280 & 50.568 \end{array}$	

Table 60 Alkaline Cleaning Rinse For Forged Parts

PSES		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	5.562 24.019 1.896 24.272 18.457 8.217 252.840	2.275 12.642 1.643 16.055 7.711 4.298 151.704

⁽¹⁾ For alternate monitoring

Table 61 Alkaline Cleaning Bath

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,00 off-pounds) of copper or copper alloy alkaline cleaned	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	0.020 0.088 0.0070 0.089 0.068 0.030 0.93	0.0084 0.046 0.0060 0.059 0.028 0.015 0.56

⁽¹⁾ For alternate monitoring

Table 62 Pickling Rinse

	0 ····	
PSES		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled	
Chromium Copper Lead Nickel Zinc TTO Oil and grease	0.574 2.481 0.195 2.507 1.906 0.848 26.120	0.235 1.306 0.169 1.658 0.796 0.444 15.672

Table 63 Pickling Rinse For Forged Parts

Telling Printe 10110 get 1 at 6		
PSES		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy forged parts pickled	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	$\begin{array}{cccc} 1.723 & 0.705 \\ 7.444 & 3.918 \\ 0.587 & 0.509 \\ 7.522 & 4.975 \\ 5.720 & 2.389 \\ 2.546 & 1.332 \\ 78.360 & 47.016 \end{array}$	

Table 64 Pickling Bath

	PSES	
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	$\begin{array}{ccc} 0.051 & 0.020 \\ 0.220 & 0.116 \\ 0.017 & 0.015 \\ 0.222 & 0.147 \\ 0.169 & 0.070 \\ 0.075 & 0.039 \\ 2.320 & 1.392 \\ \end{array}$	

Table 65 Pickling Fume Scrubber

PSES		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,00 off-pounds) of copper or coppe alloy pickled	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	0.275 1.189 0.093 1.201 0.913 0.406 12.520	0.112 0.626 0.081 0.795 0.381 0.212 7.512

Table 66 Tumbling or Burnishing

PSES		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy tumbled or burnished	
Chromium	0.256	0.104
Copper	1.107	0.583
Lead	0.087	0.075
Nickel	1.119	0.740
Zine	0.851	0.355
TTO	0.378	0.198
Oil and grease(1)	11.660	6.996

Table 67 Surface Coating

PSES		
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy surface coated	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	$\begin{array}{cccc} 0.326 & 0.133 \\ 1.411 & 0.743 \\ 0.111 & 0.096 \\ 1.426 & 0.943 \\ 1.084 & 0.453 \\ 0.482 & 0.252 \\ 14.860 & 8.916 \\ \end{array}$	

Table 68 Miscellaneous Waste Streams

PSES		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy formed	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	$\begin{array}{cccc} 0.009 & 0.003 \\ 0.041 & 0.021 \\ 0.003 & 0.002 \\ 0.041 & 0.027 \\ 0.031 & 0.013 \\ 0.014 & 0.007 \\ 0.436 & 0.261 \\ \end{array}$	

⁽¹⁾ For alternate monitoring

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89

NR 253.15 Pretreatment standards for new sources. Except as provided in s. NR 211.13, any existing source subject to this subchapter which introduces pollutants into a POTW shall comply with ch. NR 211 and achieve the following PSNS:

Table 69 Hot Rolling Spent Lubricant

PSNS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy hot rolled	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	0.038 0.131 0.010 0.056 0.105 0.035 1.030	0.015 0.062 0.0092 0.038 0.043 0.035 1.030

⁽¹⁾ For alternate monitoring

Table 70 Cold Rolling Spent Lubricant

PSNS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy cold rolled	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	$\begin{array}{cccc} 0.140 & 0.056 \\ 0.485 & 0.231 \\ 0.037 & 0.034 \\ 0.208 & 0.140 \\ 0.386 & 0.159 \\ 0.128 & 0.128 \\ 3.790 & 3.790 \\ \end{array}$	

Table 71
Drawing Spent Lubricant(1)

PSNS		
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy drawn	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(2)	0.031 0.108 0.0085 0.046 0.086 0.028 0.850	0.012 0.051 0.0076 0.031 0.035 0.028 0.850

- (1) These standards are applicable only to those plants which actually discharge the drawing spent lubricant waste stream at the copper forming site. If these wastewaters are hauled off-site for disposal or are otherwise not discharged at the copper forming site, these standards are neither applicable nor allowable.
- (2) For alternate monitoring

Table 72 Solution Heat Treatment

	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated	
Chromium	0.239	0.096
Copper	0.826	0.394
Lead	0.064	0.058
Nickel	0.355	0.239
Zinc	0.658	0.271
TTO	0.219	0.219
Oil and grease(1)	6.460	6.460

⁽¹⁾ For alternate monitoring

Table 73 Extrusion Heat Treatment

PSNS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy heat treated	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	0.00074 0.0020 0.00020 0.0010 0.0020 0.0068 0.020	0.00030 0.0010 0.00018 0.00074 0.00084 0.00068 0.020

⁽¹⁾ For alternate monitoring

Table 74 Annealing With Water

PSNS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy annealed with water	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	0.458 1.587 0.124 0.682 1.264 0.421 12.400	0.186 0.756 0.111 0.458 0.520 0.421 12.400

Table 75 Annealing With Oil

PSNS			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy annealed with oil		
Chromium	0 0		
Copper	0	0	
Lead	0	0	
Nickel	0	0	
Zinc	0	0	
TTO	0	0	
Oil and grease(1)	0	0	

Table 76 Alkaline Cleaning Rinse

	•	
PSNS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	1.559 0.632 5.393 2.570 0.421 0.379 2.317 1.559 4.298 1.769 1.432 1.432 42.140 42.140	

Table 77 Alkaline Cleaning Rinse For Forged Parts

PSNS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	4.677 16.181 1.264 6.953 12.894 4.298 126.420	1.896 7.711 1.137 4.677 5.309 4.298 126.420

Table 78 Alkaline Cleaning Bath

PSNS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy alkaline cleaned	
Chromium	0.017	0.0070
Copper	0.059	0.028
Lead	0.0046	0.0042
Nickel	0.025	0.017
Zinc	0.047	0.019
TTO	0.015	0.015
Oil and grease(1)	0.46	0.46

Table 79 Pickling Rinse

PSNS		
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	0.216 0.748 0.058 0.321 0.596 0.198 5.850	0.087 0.356 0.052 0.216 0.245 0.198 5.850

Table 80 Pickling Rinse For Forged Parts

PSNS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy forged parts pickled	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	0.649 2.246 0.175 0.965 1.790 0.596 17.550	0.263 1.070 0.157 0.649 0.737 0.596 17.550

⁽¹⁾ For alternate monitoring

Table 81 Pickling Bath

PSNS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,00 off-pounds) of copper or copper alloy pickled	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	0.042 0.148 0.011 0.063 0.118 0.039 1.160	0.017 0.070 0.010 0.042 0.048 0.039 1.160

⁽¹⁾ For alternate monitoring

Table 82 Pickling Fume Scrubber

PSNS		
	Maximum for any 1 day	Maximum for monthly average
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy pickled	
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	0.231 0.801 0.062 0.344 0.638 0.212 6.260	0.093 0.381 0.056 0.231 0.262 0.212 6.260

Table 83 Tumbling or Burnishing

PSNS			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy tumbled or burnished		
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	0.215 0.746 0.058 0.320 0.594 0.198 5.830	0.087 0.355 0.052 0.215 0.244 0.198 5.830	

Table 84 Surface Coating

PSNS			
	Maximum for any 1 day	Maximum for monthly average	
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy surface coated		
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	0.274 0.951 0.074 0.408 0.757 0.252 7.430	0.111 0.453 0.066 0.274 0.312 0.252 7.430	

(1) For alternate monitoring

Table 85 Miscellaneous Waste Streams

PSNS				
	Maximum for any 1 day	Maximum for monthly average		
Pollutant or pollutant property	mg/off-kg (pounds per 1,000,000 off-pounds) of copper or copper alloy formed			
Chromium Copper Lead Nickel Zinc TTO Oil and grease(1)	0.008 0.027 0.0021 0.011 0.022 0.007 0.218	0.003 0.013 0.0019 0.008 0.009 0.007 0.218		

(1) For alternate monitoring

History: Cr. Register, May, 1989, No. 401, eff. 6-1-89

Subchapter II — The berylium copper forming subcategory

[Reserved]

Note: The Wisconsin administrative code corresponds to the code of federal regulations as cross referenced in the following table: $\frac{1}{2} \int_{-\infty}^{\infty} \frac{1}{2} \int_{-$

State Code	Corresponding Federal Regulation
s. NR 205.03	40 C.F.R. s. 401.11
s. NR 205.04	40 C.F.R. s. 401.11
ch. NR 211	40 C.F.R. Part 403
s. NR 211.03	40 C.F.R. s. 403.03
s. NR 211.13	40 C.F.R. s. 403.7
s. NR 211.14	40 C.F.R. s. 403.13
ch. NR 253	40 C.F.R. Part 468
ch. NR 256	40 C.F.R. Part 464