

## Chapter NR 460

## EMISSION STANDARDS FOR HAZARDOUS AIR POLLUTANTS FOR SOURCE CATEGORIES-GENERAL PROVISIONS

NR 460.01	Applicability; purpose.	NR 460.06	Performance testing requirements.
NR 460.02	Definitions.	NR 460.07	Monitoring requirements.
NR 460.03	Units and abbreviations.	NR 460.08	Notification requirements.
NR 460.04	Prohibited activities and circumvention.	NR 460.09	Recordkeeping and reporting requirements.
NR 460.05	Compliance with standards and maintenance requirements.	NR 460.10	Control device requirements.

**NR 460.01 Applicability; purpose. (1) APPLICABILITY.**

(a) This chapter applies to the owner or operator of any facility affected by a standard promulgated by EPA under section 112 of the act (42 USC 7412), except as otherwise specified in the appendices of this chapter and as provided in pars. (b) and (d).

**Note:** The general provisions of this chapter eliminate the repetition of requirements applicable to all owners or operators affected by the national emission standards for hazardous air pollutants promulgated under 40 CFR part 63, which are commonly called MACT standards. These standards will regulate specific categories of stationary sources that emit, or have the potential to emit, one or more hazardous air pollutants listed pursuant to section 112 (b) of the act (42 USC 7412 (b)). The department plans to group the source categories it regulates under chs. NR 460 to 469. The likely standards to be included in chs. NR 460 to 469 by the year 2003 include fuel combustion, metals processing, chromium electroplating and anodizing, pulp and paper production, wood furniture manufacturing, printing and publishing, surface coating processes, dry cleaning, and halogenated solvent cleaning.

Some delay may occur between the promulgation of the federal standard in 40 CFR part 63 and subsequent promulgation of the standard in chs. NR 460 to 469. Permits under ch. NR 406 or 407 may, under s. 285.65, Stats., specify applicable requirements from 40 CFR part 63 and refer to applicable requirements in this chapter before the specific requirements for the source category can be promulgated in chs. NR 460 to 469.

To obtain the most current list of categories of sources to be regulated under section 112 of the act (42 USC 7412), or to obtain the most recent regulation promulgation schedule established pursuant to section 112 (e) of the act (42 USC 7412 (e)), contact the department's Bureau of Air Management, PO Box 7921, Madison WI 53707, telephone number (608) 266-7718, or EPA's Emissions Standards Division (MD-13), U.S. EPA, Office of Air Quality Planning and Standards, Research Triangle Park NC 27711, telephone number (919) 541-2380.

(b) Special provisions in a relevant standard established under 40 CFR part 63 after March 16, 1994 shall supersede any conflicting provisions of this chapter.

**Note:** This paragraph addresses federal MACT standards that have not yet been promulgated by the department under chs. NR 460 to 469. Standards established under 40 CFR part 63 include a table that identifies special provisions which supersede the general provisions of 40 CFR part 63 Subpart A. This table in the federal standard will be used as a guide for identifying special provisions that supersede comparable provisions of this chapter.

(c) If the owner or operator of an existing source obtains a compliance date extension for the source in accordance with the provisions of 40 CFR part 63, Subpart D, the owner or operator shall comply with all requirements of this chapter except those requirements that are specifically overridden in the extension of the compliance for that source.

**Note:** Extensions under the early reduction program of 40 CFR part 63, Subpart D, are only available from EPA.

(d) This chapter does not apply to the owner or operator of any facility subject to the provisions of s. NR 468.20.

(e) All references to 40 CFR part 60, 40 CFR part 61 and 40 CFR part 63 in this chapter mean those parts of the code of federal regulations as in effect on July 1, 1996, with the following exceptions:

1. In par. (b), 40 CFR part 63 means that part as it exists on the effective date of the relevant federal standard, including future standards.

2. In the case of CFR appendices incorporated by reference in ch. NR 484, if a more recent date is specified in the applicable section of ch. NR 484, that date shall apply.

**(2) PURPOSE.** Chapters NR 460 to 469 are adopted to enable the department to implement and enforce standards for stationary sources promulgated by EPA under section 112 of the act (42

USC 7412), as required by ss. 285.27 (2) and 285.65, Stats. This chapter is adopted under ss. 285.11, 285.13 and 285.17, Stats., to establish general provisions for notification, recordkeeping, monitoring and reporting requirements for sources of hazardous air contaminants.

**Note:** This chapter is based on federal regulations contained in 40 CFR part 63 Subpart A as last revised on September 1, 1995. In addition to meeting the requirements of this chapter, any major new or reconstructed source subject to a relevant standard under 40 CFR part 63 is required to obtain a construction permit under ch. NR 406 as indicated in s. NR 406.04 (2) (i). Also, most other new or modified sources are required to submit an operation permit application before commencing operation under s. NR 407.04 (1) (b) 3.

**History:** Cr. Register, March, 1997, No. 495, eff. 4-1-97; am. (2), Register, November, 1999, No. 527, eff. 12-1-99.

**NR 460.02 Definitions.** For terms not defined in this section, the definitions contained in ch. NR 400 apply to the terms used in this chapter. In addition, the definitions in this section apply to the terms used in this chapter and, for terms not defined in chs. NR 460 to 469, to the terms used in those chapters as well. If this section defines a term which is also defined in ch. NR 400, the definition in this section applies in this chapter and in chs. NR 460 to 469 rather than the definition in ch. NR 400.

**(1) "Affected source"** means the stationary source, the group of stationary sources, or the portion of a stationary source that is regulated by a relevant standard or other requirement established pursuant to section 112 of the act (42 USC 7412). Each relevant standard may further define the "affected source" for the purposes of that standard.

**(2) "Alternative emission limitation"** means conditions established pursuant to section 112 (i) (5) or (6) of the act (42 USC 7412 (i) (5) or (6)) by the department.

**(3) "Alternative emission standard"** means an alternative, at least equivalent means of emission limitation as determined by the administrator.

**Note:** The procedure under which approval of an alternative emission standard may be requested is given in 40 CFR 63.6(g).

**(4) "Alternative test method"** means any method of sampling and analyzing for an air pollutant that has been demonstrated to the department's satisfaction, using Method 301 in Appendix A of 40 CFR part 63, incorporated by reference in s. NR 484.04, to produce results adequate for the department's determination of compliance when used in place of a test method specified in chs. NR 460 to 469.

**(5) "Area source"** means any stationary source of hazardous air pollutants that is not a major source as defined in this chapter or chs. NR 460 to 469.

**(6) "Commenced"** means, with respect to construction or reconstruction of a stationary source, that an owner or operator has undertaken a continuous program of construction or reconstruction or that an owner or operator has entered into a contractual obligation with persons who have agreed to undertake and complete, within a reasonable time, a continuous program of construction or reconstruction.

**(7) "Compliance date"** means the date by which an affected source is required to be in compliance with a relevant standard,

limitation, prohibition, or any federally enforceable requirement established by the department under chs. NR 406, 407 or 460 to 469 pursuant to section 112 of the act (42 USC 7412).

**(8)** "Compliance plan" means a plan that contains all of the following:

(a) A description of the compliance status of the affected source with respect to all applicable requirements established under 40 CFR part 63.

(b) A description as follows:

1. For applicable requirements for which the source is in compliance, a statement that the source will continue to comply with the requirements.

2. For applicable requirements that the source is required to comply with by a future date, a statement that the source will meet the requirements on a timely basis.

3. For applicable requirements for which the source is not in compliance, a narrative description of how the source will achieve compliance with the requirements on a timely basis.

(c) A compliance schedule, as defined in this section.

(d) A schedule for the submission of certified progress reports no less frequently than every 6 months for affected sources required to have a schedule of compliance to remedy a violation.

**(9)** "Compliance schedule" means any of the following:

(a) In the case of an affected source that is in compliance with all applicable requirements established under 40 CFR part 63, a statement that the source will continue to comply with the requirements.

(b) In the case of an affected source that is required to comply with applicable requirements by a future date, a statement that the source will meet the requirements on a timely basis and, if required by an applicable requirement, a detailed schedule of the dates by which each step toward compliance will be reached.

(c) In the case of an affected source not in compliance with all applicable requirements established under 40 CFR part 63, a schedule of remedial measures, including an enforceable sequence of actions or operations with milestones and a schedule for the submission of certified progress reports, where applicable, leading to compliance with a relevant standard, limitation, prohibition or any federally enforceable requirement established pursuant to section 112 of the act (42 USC 7412) for which the affected source is not in compliance. This compliance schedule shall resemble and be at least as stringent as that contained in any judicial consent decree or administrative order to which the source is subject. Any schedule of compliance shall be supplemental to, and may not sanction noncompliance with, the applicable requirements on which it is based.

**(10)** "Construction" means the on-site fabrication, erection or installation of an affected source.

**(11)** "Continuous emission monitoring system" or "CEMS" means the total equipment that may be required to meet the data acquisition and availability requirements of 40 CFR part 63, used to sample, condition, if applicable, analyze and provide a record of emissions.

**(12)** "Continuous monitoring system" or "CMS" means a continuous emission monitoring system, continuous opacity monitoring system, continuous parameter monitoring system, or other manual or automatic monitoring that is used for demonstrating compliance with an applicable regulation on a continuous basis.

**(13)** "Continuous opacity monitoring system" or "COMS" means a continuous monitoring system that measures the opacity of emissions.

**(14)** "Continuous parameter monitoring system" means the total equipment that may be required to meet the data acquisition and availability requirements of 40 CFR part 63, used to sample, condition, if applicable, analyze and provide a record of process or control system parameters.

**(15)** "Effective date" means either of the following:

(a) With regard to an emission standard established under 40 CFR part 63, the date of promulgation in the federal register of the standard.

(b) With regard to an alternative emission limitation or equivalent emission limitation determined by the administrator, the date that the alternative emission limitation or equivalent emission limitation becomes effective according to the provisions of 40 CFR part 63.

**(16)** "Emission standard" means a national standard, limitation, prohibition or other regulation promulgated in a subpart of 40 CFR part 63 or in chs. NR 460 to 469 pursuant to section 112 (d), (h) or (f) of the act (42 USC 7412 (d), (h) or (f)).

**(17)** "Emissions averaging" means a way to comply with the emission limitations specified in a relevant standard, whereby an affected source, if allowed under a subpart of 40 CFR part 63, may create emission credits by reducing emissions from specific points to a level below that required by the relevant standard, and those credits are used to offset emissions from points that are not controlled to the level required by the relevant standard.

**(18)** "Equivalent emission limitation" means the maximum achievable control technology emission limitation for hazardous air pollutants that the department determines on a case-by-case basis, pursuant to section 112 (g) or (j) of the act (42 USC 7412 (g) or (j)), to be equivalent to the emission standard that would apply to an affected source if the standard had been promulgated by the administrator under 40 CFR part 63 pursuant to section 112 (d) or (h) of the act (42 USC 7412 (d) or (h)).

**(19)** "Excess emissions and continuous monitoring system performance report" means a report that shall be submitted periodically to the department by an affected source in order to provide data on its compliance with relevant emission limits, operating parameters, and the performance of its continuous parameter monitoring systems.

**(20)** "Existing source" means any affected source that is not a new MACT source.

**(21)** "Fugitive emissions" means those emissions from a stationary source that could not reasonably pass through a stack, chimney, vent or other functionally equivalent opening. Under section 112 of the act (42 USC 7412), all fugitive emissions are to be considered in determining whether a stationary source is a major source.

**(22)** "Hazardous air pollutant" means any air pollutant included in the list in section 112 (b) (1) of the act (42 USC 7412 (b) (1)) as revised by 40 CFR part 63 Subpart C.

**(23)** "Lesser quantity" means a quantity of a hazardous air pollutant that is or may be emitted by a stationary source that the administrator establishes in order to define a major source under an applicable subpart of 40 CFR part 63.

**(24)** "Major source" means any stationary source or group of stationary sources located within a contiguous area and under common control that emits or has the potential to emit considering controls, in the aggregate, 10 tons per year or more of any hazardous air pollutant or 25 tons per year or more of any combination of hazardous air pollutants, unless the administrator establishes a lesser quantity, or in the case of radionuclides, different criteria from those specified in this definition.

**(25)** "New MACT source" means any affected source the construction or reconstruction of which is commenced after the administrator first proposes a relevant emission standard under 40 CFR part 63.

**(26)** "One-hour period", unless otherwise defined in an applicable subpart of 40 CFR part 63 or in an applicable provision of chs. NR 460 to 469, means any 60-minute period commencing on the hour.

**(27)** "Opacity" means the degree to which emissions reduce the transmission of light and obscure the view of an object in the

background. For continuous opacity monitoring systems, opacity means the fraction of incident light that is attenuated by an optical medium.

**(28)** "Part 70 permit" means any permit issued, renewed or revised under ch. NR 407 for a part 70 source as defined in s. NR 407.02.

**(29)** "Performance audit" means a procedure to analyze blind samples, the content of which is known by the department, simultaneously with the analysis of performance test samples in order to provide a measure of test data quality.

**(30)** "Performance evaluation" means the conduct of relative accuracy testing, calibration error testing, and other measurements used in validating the continuous monitoring system data.

**(31)** "Performance test" means the collection of data resulting from the execution of a test method, usually 3 emission test runs, used to demonstrate compliance with a relevant emission standard as specified in the performance test section of the relevant standard.

**(32)** "Reconstruction" means the replacement of components of an affected source, or a stationary source that previously was not an affected source, to such an extent that all of the following apply:

(a) The fixed capital cost of the new components exceeds 50% of the fixed capital cost that would be required to construct a comparable new MACT source.

(b) It is technologically and economically feasible for the reconstructed source to meet the relevant standards established by the administrator or by the department pursuant to section 112 of the act (42 USC 7412). Upon reconstruction, an affected source, or a stationary source that becomes an affected source, is subject to relevant standards for new MACT sources, including compliance dates, irrespective of any change in emissions of hazardous air pollutants from that source.

**(33)** "Regulation promulgation schedule" means the schedule for the promulgation of emission standards under 40 CFR part 63, established by the administrator pursuant to section 112 (e) of the act (42 USC 7412 (e)) and published in the federal register.

**(34)** (a) "Relevant standard" means any of the following established pursuant to section 112 of the act (42 USC 7412) that applies to the stationary source, the group of stationary sources, or the portion of a stationary source regulated by the standard or limitation:

1. An emission standard.
2. An alternative emission standard.
3. An alternative emission limitation.
4. An equivalent emission limitation.

(b) A relevant standard may include or consist of a design, equipment, work practice or operational requirement, or other measure, process, method, system or technique, including prohibition of emissions, that the administrator or the department establishes for new or existing sources to which the standard or limitation applies. Every relevant standard established pursuant to section 112 of the act (42 USC 7412) includes Subpart A of 40 CFR part 63 and all applicable appendices of 40 CFR part 63 or other parts of title 40 of the code of federal regulations that are referenced in that standard.

**(35)** "Run" means one of a series of emission or other measurements needed to determine emissions for a representative operating period or cycle as specified in chs. NR 460 to 469.

**(36)** "Shutdown" means the cessation of operation of an affected source for any purpose.

**(37)** "Six-minute period" means, with respect to opacity determinations, any one of the 10 equal parts of a 1-hour period.

**(38)** "Test method" or "method" means the validated procedure for sampling, preparing and analyzing for an air pollutant specified in a relevant standard as the performance test procedure. The test method may include methods described in an appendix

of title 40 of the code of federal regulations which has been incorporated by reference in s. NR 484.04 for chs. NR 460 to 469, or methods validated for an application through procedures in Method 301 of Appendix A of 40 CFR part 63 which is incorporated by reference in s. NR 484.04.

**(39)** "Visible emission" means the observation of an emission of opacity or optical density above the threshold of vision.

**History:** Cr. Register, March, 1997, No. 495, eff. 4-1-97.

**NR 460.03 Units and abbreviations.** The definitions contained in s. NR 400.03 apply to the abbreviations and symbols of units of measure used in chs. NR 460 to 469. In addition, the following definitions apply to the units and abbreviations used in chs. NR 460 to 469:

**(1)** System International units of measure:

(a) MJ – megajoule =  $10^6$  joule

**(2)** Other units of measure:

(a) cal – calorie

(b) g–eq – gram equivalent

(c) g–mole – gram mole

(d) K = 1,000

(e) kcal – kilocalorie

(f) meq – milliequivalent

(g) ppb – parts per billion

(h) ppbv – parts per billion by volume

(i) ppbw – parts per billion by weight

(j) ppmw – parts per million by weight

(k) scf – cubic feet at standard conditions

(L) scfh – cubic feet at standard conditions per hour

(m) scm – cubic meter at standard conditions

(n) sec – second

(o) std – at standard conditions

**(3)** Miscellaneous:

(a) avg – average

(b) CEMS – continuous emission monitoring system

(c) CMS – continuous monitoring systems

(d) COMS – continuous opacity monitoring system

(e) M – molar

**History:** Cr. Register, March, 1997, No. 495, eff. 4-1-97.

**NR 460.04 Prohibited activities and circumvention.**

**(1) PROHIBITED ACTIVITIES.** (a) No owner or operator subject to the provisions of chs. NR 460 to 469 may operate any affected source in violation of the requirements of chs. NR 460 to 469 except under any of the following:

1. A compliance date extension granted by the administrator under 40 CFR part 63.

2. A compliance date extension granted under chs. NR 460 to 469 by the department.

3. An exemption from compliance granted by the president of the United States under section 112 (i) (4) of the act (42 USC 7412 (i) (4)).

(b) No owner or operator subject to the provisions of chs. NR 460 to 469 may fail to keep records, notify, report or revise reports as required under chs. NR 460 to 469.

(c) No owner or operator of an affected source who is required under 40 CFR part 63 to obtain a part 70 permit may operate the source except in compliance with the provisions of chs. NR 406, 407 and 460 to 469.

(d) An owner or operator of an affected source who is subject to an emission standard promulgated under chs. NR 460 to 469 shall comply with the requirements of that standard by the dates established in the applicable chapter regardless of any of the following:

1. A part 70 permit has been issued to that source.



2. If a part 70 permit has been issued to that source, whether the permit has been revised or modified to incorporate the emission standard.

**(2) CIRCUMVENTION.** No owner or operator subject to the provisions of chs. NR 460 to 469 may build, erect, install or use any article, machine, equipment or process to conceal an emission that would otherwise constitute noncompliance with a relevant standard. Concealment includes, but is not limited to, all of the following:

(a) The use of diluents to achieve compliance with a relevant standard based on the concentration of a pollutant in the effluent discharged to the atmosphere.

(b) The use of gaseous diluents to achieve compliance with a relevant standard for visible emissions.

(c) The fragmentation of an operation such that the operation avoids regulation by a relevant standard.

**History:** Cr. Register, March, 1997, No. 495, eff. 4-1-97.

**NR 460.05 Compliance with standards and maintenance requirements.** **(1) APPLICABILITY.** (a) The requirements in this section apply to any of the following unless the administrator or the department has granted a compliance date extension consistent with sub. (7); or the president of the United States has granted an exemption from compliance with any relevant standard in accordance with section 112 (i) (4) of the act (42 USC 7412 (i) (4)):

1. Owners or operators of affected sources for which any relevant standard has been established under chs. NR 460 to 469.

2. Owners or operators of affected sources for which any relevant standard has been established pursuant to section 112 of the act (42 USC 7412), which require a permit under ch. NR 406 or 407, after EPA program delegation to the department under section 112 (l) of the act (42 USC 7412 (l)).

**Note:** Under s. 285.65(13), Stats., all applicable requirements (including federal requirements) are included in a sources permit under chs. NR 406 and 407. After EPA approves this chapter as part of the state program qualifying for delegation under section 112 (l) of the act (42 USC 7412 (l)), this chapter would be cited in permits in lieu of 40 CFR part 63, Subpart A.

(b) If an area source, that otherwise would be subject to an emission standard or other requirement established under 40 CFR part 63 or under chs. NR 460 to 469 if it were a major source, subsequently increases its emissions of hazardous air pollutants, or its potential to emit hazardous air pollutants, such that the source is a major source, the source shall be subject to the relevant emission standard or other requirement.

**(2) COMPLIANCE DATES FOR NEW AND RECONSTRUCTED SOURCES.** (a) Except as specified in pars. (c) and (d), the owner or operator of a new or reconstructed source that has an initial startup before the effective date of a relevant standard established under 40 CFR part 63 pursuant to section 112 (d), (f) or (h) of the act (42 USC 7412 (d), (f) or (h)) shall comply with the standard not later than the standard's effective date.

(b) Except as specified in pars. (c) and (d), the owner or operator of a new or reconstructed source that has an initial startup after the effective date of a relevant standard established under 40 CFR part 63 pursuant to section 112 (d), (f) or (h) of the act (42 USC 7412 (d), (f) or (h)) shall comply with the standard upon startup of the source.

(c) The owner or operator of an affected source for which construction or reconstruction is commenced after the proposal date of a relevant standard established under 40 CFR part 63 pursuant to section 112 (d), (f) or (h) of the act (42 USC 7412 (d), (f) or (h)) but before federal promulgation of the standard shall comply with the relevant emission standard not later than the date 3 years after the federal promulgation date if:

1. The promulgated standard, that is, the relevant standard, is more stringent than the proposed federal standard.

2. The owner or operator complies with the standard as proposed during the 3-year period immediately after the effective date.

(d) The owner or operator of an affected source for which construction or reconstruction is commenced after the proposal date of a relevant standard established pursuant to section 112 (d) of the act (42 USC 7412(d)) but before the proposal date of a relevant standard established pursuant to section 112 (f) (42 USC 7412 (f)) shall comply with the emission standard under section 112 (f) not later than the date 10 years after the date construction or reconstruction is commenced, except that, if the section 112(f) standard is promulgated more than 10 years after construction or reconstruction is commenced, the owner or operator shall comply with the standard as provided in pars. (a) and (b).

(e) The owner or operator of a new MACT source that is subject to the compliance requirements of par. (c) or (d) shall notify the department in accordance with s. NR 460.08 (4).

(f) After the effective date of an emission standard promulgated under 40 CFR part 63, the owner or operator of an area source that is not an affected source for which construction or reconstruction was commenced after the proposal date of the standard that increases its emissions of, or its potential to emit, hazardous air pollutants such that the source becomes a major source that is subject to the emission standard, shall ensure that the source complies with the relevant emission standard immediately upon becoming a major source. This compliance date shall apply to new MACT sources that are area sources that become affected major sources regardless of whether the new area source previously was affected by that standard. The new affected major source shall comply with all requirements of that standard that affect new MACT sources.

**(3) COMPLIANCE DATES FOR EXISTING SOURCES.** (a) After the effective date of a relevant standard established under 40 CFR part 63 pursuant to section 112 (d) or (h) of the act (42 USC 7412 (d) or (h)), the owner or operator of an existing source shall comply with the standard by the compliance date established in the applicable subparts of 40 CFR part 63.

**Note:** Except as otherwise provided for in section 112 of the act (42 USC 7412), the compliance date established for an existing source in an applicable subpart of 40 CFR part 63 will not exceed 3 years after the effective date of the standard.

(b) After the effective date of a relevant standard established under 40 CFR part 63 pursuant to section 112 (f) of the act (42 USC 7412 (f)), the owner or operator of an existing source shall comply with the standard not later than 90 days after the standard's effective date unless the department has granted an extension to the source under sub. (7) (c) 2.

(c) 1. After the effective date of an emission standard promulgated under 40 CFR part 63, the owner or operator of an area source that is an existing source and is not an affected source that increases its emissions of, or its potential to emit, hazardous air pollutants such that the source becomes a major source that is subject to the emission standard shall comply by the date specified in the standard for area sources that are existing sources that become major sources. If no compliance date is specified in the standard, the source shall have a period of time to comply with the relevant emission standard that is equivalent to the compliance period specified in that standard for other existing sources. This compliance period shall apply to existing sources that are area sources that become affected major sources regardless of whether the existing area source previously was affected by that standard.

2. Notwithstanding subd. 1., if the existing source that is an area source becomes a major source by the addition of a new affected source or by reconstructing, the portion of the existing facility that is a new affected source or a reconstructed source shall comply with all requirements of that standard that affect new MACT sources, including the compliance date for new MACT sources.

**(4) OPERATION AND MAINTENANCE REQUIREMENTS.** (a) *General.* 1. At all times, including periods of startup, shutdown, and malfunction, owners or operators shall operate and maintain any affected source, including associated air pollution control equipment, in a manner consistent with good air pollution control practices for minimizing emissions at least to the levels required by all relevant standards.

2. Malfunctions shall be corrected as soon as practicable after their occurrence in accordance with the startup, shutdown and malfunction plan required in par. (c).

3. Operation and maintenance requirements established pursuant to section 112 of the act (42 USC 7412) are enforceable independent of emissions limitations or other requirements in relevant standards.

(b) *Basis for acceptance.* Determination of whether acceptable operation and maintenance procedures are being used will be based on information available to the department which may include, but is not limited to, monitoring results, review of operation and maintenance procedures, including the startup, shutdown and malfunction plan required in par. (c), review of operation and maintenance records, and inspection of the source.

(c) *Startup, shutdown and malfunction plan.* 1. In addition to the requirements of s. NR 439.11, the owner or operator of an affected source shall develop and implement a written startup, shutdown and malfunction plan that describes, in detail, procedures for operating and maintaining the source during periods of startup, shutdown and malfunction and a program of corrective action for malfunctioning process and air pollution control equipment used to comply with the relevant standard. As required under s. NR 460.07 (3) (a) 1., the plan shall identify all routine or otherwise predictable continuous monitoring system malfunctions. This plan shall be developed by the owner or operator by the source's compliance date for that relevant standard. The plan shall be incorporated by reference into the source's part 70 permit.

**Note:** The purpose of the startup, shutdown and malfunction plan is to achieve all of the following:

a. Ensure that, at all times, owners or operators operate and maintain affected sources, including associated air pollution control equipment, in a manner consistent with good air pollution control practices for minimizing emissions at least to the levels required by all relevant standards.

b. Ensure that owners or operators are prepared to correct malfunctions as soon as practicable after their occurrence in order to minimize excess emissions of hazardous air pollutants.

c. Reduce the reporting burden associated with periods of startup, shutdown, and malfunction (including corrective action taken to restore malfunctioning process and air pollution control equipment to its normal or usual manner of operation).

2. During periods of startup, shutdown and malfunction, the owner or operator of an affected source shall operate and maintain the source, including associated air pollution control equipment, in accordance with the procedures specified in the startup, shutdown and malfunction plan developed under subd. 1.

3. When actions taken by the owner or operator during a startup, shutdown or malfunction, including actions taken to correct a malfunction, are consistent with the procedures specified in the affected source's startup, shutdown and malfunction plan, the owner or operator shall keep records for that event that demonstrate that the procedures specified in the plan were followed. In addition, the owner or operator shall keep records of these events as specified in s. NR 460.09 (2), and elsewhere in 40 CFR part 63 and in chs. NR 460 to 469, including records of the occurrence and duration of each startup, shutdown or malfunction of operation and each malfunction of the air pollution control equipment. Furthermore, the owner or operator shall confirm that actions taken during the relevant reporting period during periods of startup, shutdown and malfunction were consistent with the affected source's startup, shutdown and malfunction plan in the semi-annual, or more frequent, startup, shutdown and malfunction report required in s. NR 460.09 (4) (e).

4. If an action taken by the owner or operator during a startup, shutdown or malfunction, including an action taken to correct a

malfunction, is not consistent with the procedures specified in the affected source's startup, shutdown and malfunction plan, the owner or operator shall record the actions taken for that event and shall report the actions within 2 working days after commencing actions inconsistent with the plan, followed by a letter within 7 working days after the end of the event, in accordance with s. NR 460.09 (4) (e), unless the owner or operator makes alternative reporting arrangements, in advance, with the department under s. NR 460.09 (4) (e) 2.

5. The owner or operator shall keep the written startup, shutdown and malfunction plan on record after it is developed to be made available for inspection, upon request, by the department for the life of the affected source or until the affected source is no longer subject to the provisions of 40 CFR part 63. In addition, if the startup, shutdown and malfunction plan is revised, the owner or operator shall keep previous versions of the startup, shutdown and malfunction plan on record, to be made available for inspection, upon request, by the department, for a period of 5 years after each revision to the plan.

6. To satisfy the requirements to develop a startup, shutdown and malfunction plan, the owner or operator may use the affected source's standard operating procedures manual, or an occupational safety and health administration or other plan, provided the alternative plans meet all the requirements of this section and are made available for inspection when requested by the department.

7. The department may require that an owner or operator of an affected source make changes to the startup, shutdown and malfunction plan for that source. The department may require reasonable revisions to a startup, shutdown and malfunction plan, if the department finds that the plan does any of the following:

a. Does not address a startup, shutdown or malfunction event that has occurred.

b. Fails to provide for the operation of the source, including associated air pollution control equipment, during a startup, shutdown or malfunction event in a manner consistent with good air pollution control practices for minimizing emissions at least to the levels required by all relevant standards.

c. Does not provide adequate procedures for correcting malfunctioning process and air pollution control equipment as quickly as practicable.

8. If the startup, shutdown and malfunction plan fails to address or inadequately addresses an event that meets the characteristics of a malfunction but was not included in the startup, shutdown and malfunction plan at the time the owner or operator developed the plan, the owner or operator shall revise the startup, shutdown and malfunction plan within 45 days after the event to include detailed procedures for operating and maintaining the source during similar malfunction events and a program of corrective action for similar malfunctions of process or air pollution control equipment.

**(5) COMPLIANCE WITH NONOPACITY EMISSION STANDARDS.** The nonopacity emission standards in 40 CFR part 63 or in chs. NR 460 to 469 shall apply at all times except during periods of startup, shutdown and malfunction, and as otherwise specified in an applicable subpart of 40 CFR part 63 or in an applicable provision of chs. NR 460 to 469.

**(6) COMPLIANCE WITH OPACITY AND VISIBLE EMISSION STANDARDS.** (a) *Applicability.* The opacity and visible emission standards in 40 CFR part 63 and in chs. NR 460 to 469 shall apply at all times except during periods of startup, shutdown and malfunction, and as otherwise specified in an applicable subpart of 40 CFR part 63 or in an applicable provision of chs. NR 460 to 469.

(b) *Methods for determining compliance.* 1. a. Whenever a continuous opacity monitoring system (COMS) is required to be installed to determine compliance with numerical opacity emission standards in 40 CFR part 63 and in chs. NR 460 to 469, compliance with opacity emission standards in 40 CFR part 63 and in

chs. NR 460 to 469 shall be determined by using the results from the COMS.

b. Whenever an opacity emission test method is not specified, compliance with opacity emission standards in 40 CFR part 63 and in chs. NR 460 to 469 shall be determined by conducting observations in accordance with Method 9 in Appendix A of 40 CFR part 60, incorporated by reference in s. NR 484.04, or the method specified in par. (f) 2.

c. Whenever a visible emission test method is not specified, compliance with visible emission standards in 40 CFR part 63 and in chs. NR 460 to 469 shall be determined by conducting observations in accordance with Method 22 in Appendix A of 40 CFR part 60, incorporated by reference in s. NR 484.04.

2. If an affected source undergoes opacity or visible emission testing at startup to obtain an operation permit under ch. NR 407, the results of the testing may be used to demonstrate compliance with a relevant standard if all of the following occur:

a. The opacity or visible emission test was conducted within a reasonable amount of time before a performance test is required to be conducted under the relevant standard.

b. The opacity or visible emission test was conducted under representative operating conditions for the source.

c. The opacity or visible emission test was conducted and the resulting data were reduced using EPA-approved test methods and procedures, as specified in s. NR 460.06 (4).

d. The opacity or visible emission test was appropriately quality-assured, as specified under s. NR 460.06 (2).

(c) *Notification of opacity or visible emission observations.* The owner or operator of an affected source shall notify the department in writing of the anticipated date for conducting opacity or visible emission observations in accordance with s. NR 460.08 (6), if the observations are required for the source by a relevant standard.

(d) *Conduct of opacity or visible emission observations.* When a relevant standard under 40 CFR part 63 includes an opacity or visible emission standard, the owner or operator of an affected source shall comply with the following:

1. For the purpose of demonstrating initial compliance, opacity or visible emission observations shall be conducted concurrently with the initial performance test required in s. NR 460.06 unless one of the following conditions applies:

a. If no performance test under s. NR 460.06 is required, opacity or visible emission observations shall be conducted within 60 days after achieving the maximum production rate at which a new or reconstructed source will be operated, but not later than 120 days after initial startup of the source, or within 120 days after the effective date of the relevant standard in the case of new MACT sources that start up before the standard's effective date. If no performance test under s. NR 460.06 is required, opacity or visible emission observations shall be conducted within 120 days after the compliance date for an existing or modified source.

b. If visibility or other conditions prevent the opacity or visible emission observations from being conducted concurrently with the initial performance test required under s. NR 460.06, or within the time period specified in subd. 1. a., the source's owner or operator shall reschedule the opacity or visible emission observations as soon after the initial performance test, or time period, as possible, but not later than 30 days thereafter, and shall advise the department of the rescheduled date. The rescheduled opacity or visible emission observations shall be conducted, to the extent possible, under the same operating conditions that existed during the initial performance test conducted under s. NR 460.06. The visible emissions observer shall determine whether visibility or other conditions prevent the opacity or visible emission observations from being made concurrently with the initial performance test in accordance with procedures contained in Method 9 or

Method 22 in Appendix A of 40 CFR part 60, incorporated by reference in s. NR 484.04.

2. For the purpose of demonstrating initial compliance, the minimum total time of opacity observations shall be 3 hours, 30 6-minute averages, for the performance test or other required set of observations, including fugitive-type emission sources subject only to an opacity emission standard.

3. The owner or operator of an affected source to which an opacity or visible emission standard in 40 CFR part 63 applies shall conduct opacity or visible emission observations in accordance with the provisions of this section, record the results of the evaluation of emissions, and report to the department the opacity or visible emission results in accordance with the provisions of s. NR 460.09 (4).

4. Opacity readings of portions of plumes that contain condensed, uncombined water vapor may not be used for purposes of determining compliance with opacity emission standards.

(e) *Availability of records.* The owner or operator of an affected source shall make available, upon request by the department, records that the department deems necessary to determine the conditions under which the visual observations were made and shall provide evidence indicating proof of current visible emission observer certification.

(f) *Use of a continuous opacity monitoring system.* 1. The owner or operator of an affected source required to use a continuous opacity monitoring system (COMS) shall record the monitoring data produced during a performance test required under s. NR 460.06 and shall furnish the department a written report of the monitoring results in accordance with the provisions of s. NR 460.09 (5) (d).

2. Whenever an opacity emission test method has not been specified in an applicable subpart of 40 CFR part 63 or in an applicable provision of chs. NR 460 to 469, or an owner or operator of an affected source is required to conduct observations according to Method 9 of Appendix A of 40 CFR part 60, incorporated by reference in s. NR 484.04, the owner or operator may submit, for compliance purposes, COMS data results produced during any performance test required under s. NR 460.06 in lieu of Method 9 data. If the owner or operator elects to submit COMS data for compliance with the opacity emission standard, he or she shall notify the department of that decision, in writing, simultaneously with the notification under s. NR 460.06 (2) of the date the performance test is scheduled to begin. Once the owner or operator of an affected source has notified the department to that effect, the COMS data results will be used to determine opacity compliance during subsequent performance tests required under s. NR 460.06, unless the owner or operator notifies the department in writing to the contrary not later than with the notification under s. NR 460.06 (2) of the date the subsequent performance test is scheduled to begin.

3. For the purposes of determining compliance with the opacity emission standard during a performance test required under s. NR 460.06 using COMS data, the COMS data shall be reduced to 6-minute averages over the duration of the mass emission performance test.

4. The owner or operator of an affected source using a COMS for compliance purposes is responsible for demonstrating the performance evaluation requirements of s. NR 460.07 (5) have been met, the COMS has been properly maintained, operated and data quality-assured, as specified in s. NR 460.07 (3) and (4), and the resulting data have not been altered in any way.

5. Except as provided in subd. 2., the results of continuous monitoring by a COMS that indicate that the opacity at the time visual observations were made was not in excess of the emission standard are probative but not conclusive evidence of the actual opacity of an emission, provided that the affected source proves that, at the time of the alleged violation, the instrument used was



properly maintained, as specified in s. NR 460.07 (3), and met Performance Specification 1 in Appendix B of 40 CFR part 60, incorporated by reference in s. NR 484.04, and that the resulting data have not been altered in any way.

(g) *Finding of compliance.* The department shall make a finding concerning an affected source's compliance with an opacity or visible emission standard upon obtaining all the compliance information required by the relevant standard, including the written reports of the results of the performance tests required by s. NR 460.06, the results of Method 9 of Appendix A of 40 CFR part 60, incorporated by reference in s. NR 484.04, or another required opacity or visible emission test method, the observer certification required by par. (e), and the continuous opacity monitoring system results, whichever are applicable, and any information available to the department needed to determine whether proper operation and maintenance practices are being used.

(7) EXTENSION OF COMPLIANCE WITH EMISSION STANDARDS. (a) Until a compliance date extension has been granted by the administrator or the department under this subsection or 40 CFR 63.6(i), the owner or operator of an affected source subject to the requirements of this section shall comply with all applicable requirements of 40 CFR part 63 and chs. NR 460 to 469.

(b) Pursuant to section 112 (i) (6) of the act (42 USC 7412 (i) (6)), if the owner or operator of an existing source has installed BACT, as defined in section 169 (3) of the act (42 USC 7479 (3)), or technology required to meet a LAER, as defined in section 171 of the act (42 USC 7501), prior to the promulgation of an emission standard in 40 CFR part 63 applicable to the source and the same pollutant or stream of pollutants controlled pursuant to the BACT or LAER installation, the department may grant the owner or operator an extension of the compliance date with the emission standard that will apply until the date 5 years after the date on which the installation was achieved, as determined by the department.

**Note:** BACT and LAER are more broadly defined under s. 285.01 (12) and (23), Stats.

(c) 1. a. The owner or operator of an existing source who is unable to comply with a relevant standard established under 40 CFR part 63 pursuant to section 112 (d) of the act (42 USC 7412 (d)) may request that the department grant an extension allowing the source up to one additional year to comply with the standard, if the additional period is necessary for the installation of controls. The owner or operator of an affected source who has requested a compliance date extension under this subsection or 40 CFR 63.6 (i) and who is otherwise required to obtain a part 70 permit shall apply for the permit or apply to have the source's part 70 permit revised to incorporate the conditions of the compliance date extension. The conditions of a compliance date extension granted under this subsection will be incorporated into the affected source's part 70 permit.

**Note:** Under 40 CFR 63.6(i)(4)(i)(A), the administrator may provide an additional extension of up to 3 years for mining waste operations, if the 1-year extension of the compliance date is insufficient to dry and cover mining waste in order to reduce emissions of any hazardous air pollutant.

b. Any request under this subsection for an extension of the compliance date of a relevant standard shall be submitted in writing to the department not later than 12 months before the affected source's compliance date, as specified in subs. (2) and (3), for sources that are not including emission points in an emissions average, or not later than 18 months before the affected source's compliance date, as specified in subs. (2) and (3), for sources that are including emission points in an emissions average. Emission standards established under 40 CFR part 63 may specify alternative dates for the submittal of requests for a compliance date extension if alternatives are appropriate for the source categories affected by those standards.

2. The owner or operator of an existing source unable to comply with a relevant standard established under 40 CFR part 63 pursuant to section 112 (f) of the act (42 USC 7412 (f)) may request that the department grant an extension allowing the source up to

2 years after the standard's effective date to comply with the standard. The department may grant an extension if it finds that the additional period is necessary for the installation of controls and that steps will be taken during the extension period to assure that human health will be protected from imminent endangerment. Any request for an extension of the compliance date for a relevant standard under this subsection shall be submitted in writing to the department not later than 15 calendar days after the effective date of the relevant standard.

(d) The owner or operator of an existing source that has installed BACT or technology required to meet LAER, as specified in par. (b), prior to the promulgation of a relevant emission standard in 40 CFR part 63 may request that the department grant an extension allowing the source 5 years from the date on which the installation was achieved, as determined by the department, to comply with the standard. Any request for an extension of the compliance date for a relevant standard under this subsection shall be submitted in writing to the department not later than 120 days after the promulgation date of the standard. The department may grant an extension if it finds that the installation of BACT or technology to meet LAER controls the same pollutant or stream of pollutants that would be controlled at that source by the relevant emission standard.

(e) The request for a compliance date extension under par. (c) shall include all of the following information:

1. A description of the controls to be installed to comply with the standard.

2. A compliance schedule, including the date by which each step toward compliance will be reached. At a minimum, the list of dates shall include all of the following:

a. The date by which contracts for emission control systems or process changes for emission control will be awarded, or the date by which orders will be issued for the purchase of component parts to accomplish emission control or process changes.

b. The date by which on-site construction, installation of emission control equipment or a process change is to be initiated.

c. The date by which on-site construction, installation of emission control equipment, or a process change is to be completed.

d. The date by which final compliance is to be achieved.

3. A description of interim emission control steps that will be taken during the extension period, including milestones, to assure proper operation and maintenance of emission control and process equipment.

4. Whether the owner or operator is also requesting an extension of other applicable requirements, such as performance testing requirements.

(em) The request for a compliance extension under par. (d) shall include all information needed to demonstrate to the department's satisfaction that the installation of BACT or technology to meet LAER controls the same pollutant or stream of pollutants that would be controlled at that source by the relevant emission standard.

(f) Advice on requesting an extension of a compliance date may be obtained from the department.

(g) Based on the information provided in any request made under pars. (c) to (em), or other information, the department may grant an extension of the compliance date for an emission standard, as specified in pars. (c) and (d).

(h) An extension shall be in writing and shall do all of the following:

1. Identify each affected source covered by the extension.

2. Specify the termination date of the extension.

3. Specify the dates by which steps toward compliance are to be taken, if appropriate.

4. Specify other applicable requirements to which the compliance extension applies, such as performance tests.

5. Specify any additional conditions that the department deems necessary to assure any of the following:

a. Under par. (c), the installation of the necessary controls and protection of human health during the extension period.

b. Under par. (d), the proper operation and maintenance of the installed controls during the extension period.

(i) The owner or operator of an existing source that has been granted a compliance date extension under par. (g) may be required to submit to the department progress reports indicating whether the steps toward compliance outlined in the compliance schedule have been reached. The contents of the progress reports and the dates by which they shall be submitted shall be specified in the written compliance date extension granted under par. (h).

(j) 1. The department shall notify the owner or operator in writing of approval or intention to deny approval of a request for a compliance date extension within 30 calendar days after receipt of sufficient information to evaluate a request submitted under par. (c) 1. or (d). The 30-day approval or denial period will begin after the owner or operator has been notified in writing that the application is complete. The department shall notify the owner or operator in writing as to whether the application contains sufficient information to make a determination within 30 calendar days after receipt of the original application and within 30 calendar days after receipt of any supplementary information that is submitted.

2. When notifying the owner or operator that an application is not complete, the department shall specify the information needed to complete the application and provide notice of opportunity for the applicant to present, in writing, within 30 calendar days after notification of the incomplete application, additional information or arguments to the department to enable further action on the application.

3. Before denying any request for a compliance date extension, the department shall notify the owner or operator in writing of the department's intention to issue the denial, together with all of the following:

a. Notice of the information and findings on which the intended denial is based.

b. Notice of opportunity for the owner or operator to present in writing, within 15 calendar days after notification of the intended denial, additional information or arguments to the department before further action on the request.

4. The department's final determination to deny any request for an extension shall be in writing and shall set forth the specific grounds on which the denial is based. The final determination shall be made within 30 calendar days after presentation of additional information or argument, if the application is complete, or within 30 calendar days after the final date specified for the presentation if no presentation is made.

(k) 1. The department shall notify the owner or operator in writing of approval or intention to deny approval of a request for a compliance date extension within 30 calendar days after receipt of sufficient information to evaluate a request submitted under par. (c) 2. The 30-day approval or denial period will begin after the owner or operator has been notified in writing that the application is complete. The department shall notify the owner or operator in writing of the status of the application, that is, whether the application contains sufficient information to make a determination, within 15 calendar days after receipt of the original application and within 15 calendar days after receipt of any supplementary information that is submitted.

2. When notifying the owner or operator that an application is not complete, the department shall specify the information needed to complete the application and provide notice of opportunity for the applicant to present, in writing, within 15 calendar days after notification of the incomplete application, additional information or arguments to the department to enable further action on the application.

3. Before denying any request for a compliance date extension, the department shall notify the owner or operator in writing of the department's intention to issue the denial, together with all of the following:

a. Notice of the information and findings on which the intended denial is based.

b. Notice of opportunity for the owner or operator to present in writing, within 15 calendar days after notification of the intended denial, additional information or arguments to the department before further action on the request.

4. A final determination to deny any request for an extension shall be in writing and shall set forth the specific grounds on which the denial is based. The final determination shall be made within 30 calendar days after presentation of additional information or argument, if the application is complete, or within 30 calendar days after the final date specified for the presentation if no presentation is made.

(L) The department may terminate a compliance date extension at an earlier date than specified if any specification under par. (h) 3. or 4. is not met.

**History:** Cr. Register, March, 1997, No. 495, eff. 4-1-97.

#### **NR 460.06 Performance testing requirements.**

(1) **APPLICABILITY AND PERFORMANCE TEST DATES.** (a) Unless otherwise specified, this section applies to the owner or operator of an affected source required to do performance testing, or another form of compliance demonstration, under a relevant standard.

(b) If required to do performance testing by a relevant standard, and unless a waiver of performance testing is obtained under this section, the owner or operator of the affected source shall perform the tests according to one of the following:

1. Within 180 days after the effective date of a relevant standard for a new MACT source that has an initial startup date before the effective date.

2. Within 180 days after initial startup for a new MACT source that has an initial startup date after the effective date of a relevant standard.

3. Within 180 days after the compliance date specified in an applicable subpart of 40 CFR part 63 for an existing source subject to an emission standard established pursuant to section 112 (d) of the act (42 USC 7412 (d)), or within 180 days after startup of an existing source if the source begins operation after the effective date of the relevant emission standard.

4. Within 180 days after the compliance date for an existing source subject to an emission standard established pursuant to section 112 (f) of the act (42 USC 7412 (f)).

5. Within 180 days after the termination date of the source's extension of a compliance date for an existing source that obtains an extension under s. NR 460.05 (7).

6. Within 180 days after the compliance date for a new MACT source, subject to an emission standard established pursuant to section 112 (f) of the act (42 USC 7412 (f)), for which construction or reconstruction is commenced after the proposal date of a relevant standard established pursuant to section 112(d) of the act (42 USC 7412 (d)) but before the proposal date of the relevant standard established pursuant to section 112 (f).

7. Within 180 days after the standard's effective date, or within 180 days after startup of the source, whichever is later, when an emission standard promulgated under 40 CFR part 63 is more stringent than the standard proposed, for a new or reconstructed source subject to that standard for which construction or reconstruction is commenced between the proposal and promulgation dates of the standard. If the promulgated standard is more stringent than the proposed standard, the owner or operator may choose to demonstrate compliance with either the proposed or the promulgated standard. If the owner or operator chooses to comply with the proposed standard initially, the owner or operator



shall conduct a second performance test within 3 years and 180 days after the effective date of the standard, or after startup of the source, whichever is later, to demonstrate compliance with the promulgated standard.

**(2) DEPARTMENT OVERSIGHT OF PERFORMANCE TESTING.** Performance tests shall be conducted in accordance with s. NR 439.07 (2) to (4) and (6).

**(3) PERFORMANCE TESTING FACILITIES.** If required to do performance testing, the owner or operator of each new MACT source and, at the request of the department, the owner or operator of each existing source, shall provide all of the following performance testing facilities:

(a) Sampling ports adequate for test methods applicable to the source. This includes all of the following:

1. Constructing the air pollution control system such that volumetric flow rates and pollutant emission rates can be accurately determined by applicable test methods and procedures.

2. Providing a stack or duct free of cyclonic flow during performance tests, as demonstrated by applicable test methods and procedures.

(b) Safe sampling platforms.

(c) Safe access to sampling platforms.

(d) Utilities for sampling and testing equipment.

(e) Any other facilities that the department deems necessary for safe and adequate testing of a source.

**(4) CONDUCT OF PERFORMANCE TESTS.** (a) Performance tests shall be conducted under such conditions as the department specifies to the owner or operator based on normal, representative performance of the affected source. Operations during periods of startup, shutdown and malfunction do not constitute representative conditions for the purpose of a performance test, nor will emissions in excess of the level of the relevant standard during periods of startup, shutdown and malfunction be considered a violation of the relevant standard unless otherwise specified in the relevant standard or a determination of noncompliance is made under s. NR 460.05 (4). Upon request, the owner or operator shall make available to the department such records as may be necessary to determine the conditions of performance tests.

(b) Performance tests shall be conducted and data shall be reduced in accordance with the test methods and procedures in this section, in each relevant standard, and, if required, in applicable appendices of parts 51, 60, 61 and 63 of title 40 of the code of federal regulations unless the department does any of the following:

1. Specifies or approves, in specific cases, the use of a test method with minor changes in methodology.

2. Approves the use of an alternative test method, the results of which the department has determined to be adequate for indicating whether a specific affected source is in compliance.

3. Approves shorter sampling times and smaller sample volumes when necessitated by process variables or other factors.

4. Waives the requirement for performance tests because the owner or operator of an affected source has demonstrated by other means to the department's satisfaction that the affected source is in compliance with the relevant standard.

(c) Unless otherwise specified in a relevant standard or test method, each performance test shall consist of 3 separate runs using the applicable test method. Each run shall be conducted for the time and under the conditions specified in the relevant standard. For the purpose of determining compliance with a relevant standard, the arithmetic mean of the results of the 3 runs shall apply. Upon receiving approval from the department, results of a test run may be replaced with results of an additional test run in the event that any of the following occurs:

1. A sample is accidentally lost after the testing team leaves the site.

2. Conditions occur in which one of the 3 runs must be discontinued because of forced shutdown.

3. Extreme meteorological conditions occur.

4. Other circumstances occur that are beyond the owner or operator's control.

**(5) USE OF AN ALTERNATIVE TEST METHOD.** (a) Until permission to use an alternative test method has been granted by the department under this subsection, the owner or operator of an affected source remains subject to the requirements of this section and the relevant standard.

(b) The owner or operator of an affected source required to do performance testing by a relevant standard may use an alternative test method from that specified in the standard provided that the owner or operator does all of the following:

1. Notifies the department of his or her intention to use an alternative test method not later than with the submittal of the site-specific test plan.

2. Uses Method 301 in Appendix A of 40 CFR part 63, incorporated by reference in s. NR 484.04, to validate the alternative test method.

3. Submits the results of the Method 301 validation process along with the notification of intention and the justification for not using the specified test method. The owner or operator may submit the information required in this subsection well in advance of the deadline specified in subd. 1. to ensure a timely review by the department in order to meet the performance test date specified in this section or the relevant standard.

(c) The department shall determine whether the owner or operator's validation of the proposed alternative test method is adequate when the department approves or disapproves the site-specific test plan required under sub. (2). If the department finds reasonable grounds to dispute the results obtained by the Method 301 validation process, the department may require the use of a test method specified in a relevant standard.

(d) If the department finds reasonable grounds to dispute the results obtained by an alternative test method for the purposes of demonstrating compliance with a relevant standard, the department may require the use of a test method specified in a relevant standard.

(e) If the owner or operator uses an alternative test method for an affected source during a required performance test, the owner or operator of the source shall continue to use the alternative test method for subsequent performance tests at that affected source until he or she receives approval from the department to use another test method as allowed under this subsection.

(f) Neither the validation and approval process nor the failure to validate an alternative test method shall abrogate the owner or operator's responsibility to comply with the requirements of 40 CFR part 63 or chs. NR 460 to 469.

**(6) DATA ANALYSIS, RECORDKEEPING, AND REPORTING.** (a) Unless otherwise specified in a relevant standard or test method, or as otherwise approved by the department in writing, results of a performance test shall include the analysis of samples, determination of emissions and raw data. A performance test is "completed" when field sample collection is terminated. The owner or operator of an affected source shall report the results of the performance test to the department before the close of business on the 60th day following the completion of the performance test, unless specified otherwise in a relevant standard or as approved otherwise in writing by the department. The results of the performance test shall be submitted as part of the notification of compliance status required under s. NR 460.08 (8). The owner or operator shall send the results of the performance test to the department.

(b) For a minimum of 5 years after a performance test is conducted, the owner or operator shall retain and make available, upon request, for inspection by the department the records or

results of the performance test and other data needed to determine emissions from an affected source.

**(7) WAIVER OF PERFORMANCE TESTS.** (a) Until a waiver of a performance testing requirement has been granted by the department under this subsection, the owner or operator of an affected source remains subject to the requirements of this section.

(b) Individual performance tests may be waived upon written application to the department if, in the department's judgment, the source is meeting the relevant standards on a continuous basis, or the source is being operated under a compliance date extension, or the owner or operator has requested a compliance date extension and the department is still considering that request.

(c) 1. If a request is made for a compliance date extension under s. NR 460.05 (7), the application for a waiver of an initial performance test shall accompany the information required for the request for an extension. If no extension is requested or if the owner or operator has requested an extension and the department is still considering that request, the application for a waiver of an initial performance test shall be submitted at least 60 days before the performance test.

2. If an application for a waiver of a subsequent performance test is made, the application may accompany any required compliance progress report, compliance status report, or excess emissions and continuous monitoring system performance report, but it shall be submitted at least 60 days before the performance test.

3. Any application for a waiver of a performance test shall include information justifying the owner or operator's request for a waiver, such as the technical or economic infeasibility, or the impracticality, of the affected source performing the required test.

(d) The department shall approve or deny a request for a waiver of a performance test made under par. (c) when it does whichever of the following applies:

1. Approves or denies a compliance date extension under s. NR 460.05 (7) (g) to (L).

2. Responds to a site-specific test plan under sub. (2).

3. Makes a determination of compliance following the submission of a required compliance status report or excess emissions and continuous monitoring systems performance report.

4. Makes a determination of suitable progress towards compliance following the submission of a compliance progress report.

(e) Approval of any waiver granted under this section may not in any way prohibit the department from later canceling the waiver. The cancellation shall be made only after notice is given to the owner or operator of the affected source.

**History:** Cr. Register, March, 1997, No. 495, eff. 4-1-97.

**NR 460.07 Monitoring requirements. (1) APPLICABILITY.** (a) 1. Unless otherwise specified in a relevant standard, this section applies to the owner or operator of an affected source required to do monitoring under that standard.

2. Relevant standards established under 40 CFR part 63 or chs. NR 460 to 469 will specify monitoring systems, methods or procedures, monitoring frequency and other pertinent requirements for sources regulated by those standards. This section specifies general monitoring requirements such as those governing the conduct of monitoring and requests to use alternative monitoring methods. In addition, this section specifies detailed requirements that apply to affected sources required to use CMS under a relevant standard.

(b) For the purposes of 40 CFR part 63 and in chs. NR 460 to 469, all continuous monitoring systems required under relevant standards shall be subject to the provisions of this section upon federal promulgation of performance specifications for continuous monitoring systems as specified in the relevant standard or otherwise by the department.

(c) Additional monitoring requirements for control devices used to comply with provisions in relevant standards of 40 CFR part 63 are specified in s. NR 460.10.

**(2) CONDUCT OF MONITORING.** (a) Except as provided in par. (am), monitoring shall be conducted as set forth in this section and the relevant standards unless the department does any of the following:

1. Specifies or approves the use of minor changes in methodology for the specified monitoring requirements and procedures.

2. Approves the use of alternatives to any monitoring requirements or procedures.

(am) Owners or operators with flares subject to s. NR 460.10 (2) are not subject to the requirements of this section unless otherwise specified in the relevant standard.

(b) 1. When the effluents from a single affected source, or from 2 or more affected sources, are combined before being released to the atmosphere, the owner or operator shall install an applicable continuous monitoring system on each effluent.

2. If the relevant standard is a mass emission standard and the effluent from one affected source is released to the atmosphere through more than one point, the owner or operator shall install an applicable continuous monitoring system at each emission point unless the installation of fewer systems is any of the following:

a. Approved by the department.

b. Provided for in a relevant standard.

(c) When more than one continuous monitoring system is used to measure the emissions from one affected source, the owner or operator shall report the results as required for each continuous monitoring system. However, when one continuous monitoring system is used as a backup to another continuous monitoring system, the owner or operator shall report the results from the continuous monitoring system used to meet the monitoring requirements of 40 CFR part 63. If both continuous monitoring systems are used during a particular reporting period to meet the monitoring requirements of 40 CFR part 63, then the owner or operator shall report the results from each continuous monitoring system for the relevant compliance period.

**(3) OPERATION AND MAINTENANCE OF CONTINUOUS MONITORING SYSTEMS.** (a) The owner or operator of an affected source shall maintain and operate each CMS as specified in this section, or in a relevant standard, and in a manner consistent with good air pollution control practices.

1. The owner or operator of an affected source shall ensure the immediate repair or replacement of CMS parts to correct "routine" or otherwise predictable CMS malfunctions as defined in the source's startup, shutdown and malfunction plan required by s. NR 460.05 (4) (c). The owner or operator shall keep the necessary parts for routine repairs of the affected equipment readily available. If the plan is followed and the CMS repaired immediately, this action shall be reported in the semiannual startup, shutdown and malfunction report required under s. NR 460.09 (4) (e).

2. For those malfunctions or other events that affect the CMS and are not addressed by the startup, shutdown and malfunction plan, the owner or operator shall report actions that are not consistent with the startup, shutdown and malfunction plan within 24 hours after commencing actions inconsistent with the plan. The owner or operator shall send a follow-up report within 2 weeks after commencing actions inconsistent with the plan that either certifies that corrections have been made or includes a corrective action plan and schedule. The owner or operator shall provide proof that repair parts have been ordered or any other records that would indicate that the delay in making repairs is beyond his or her control.

3. The department's determination of whether acceptable operation and maintenance procedures are being used shall be based on information that may include, but is not limited to,

review of operation and maintenance procedures, operation and maintenance records, manufacturing recommendations and specifications, and inspection of the CMS. Operation and maintenance procedures written by the CMS manufacturer and other guidance also may be used to maintain and operate each CMS.

(b) All CMS shall be installed such that representative measurements of emissions or process parameters from the affected source are obtained. In addition, CEMS shall be located according to procedures contained in the applicable performance specifications.

(c) All CMS shall be installed, operational and the data verified as specified in the relevant standard either prior to or in conjunction with the conduct of performance tests under s. NR 460.06. Verification of operational status shall, at a minimum, include completion of the manufacturer's written specifications or recommendations for installation, operation and calibration of the system.

(d) Except for system breakdowns, out-of-control periods, repairs, maintenance periods, calibration checks, and zero (low-level) and high-level calibration drift adjustments, all CMS, including COMS and CEMS, shall be in continuous operation and shall meet minimum frequency of operation requirements as follows:

1. All COMS shall complete a minimum of one cycle of sampling and analyzing for each successive 10-second period and one cycle of data recording for each successive 6-minute period.

2. All CEMS for measuring emissions other than opacity shall complete a minimum of one cycle of operation, which includes sampling, analyzing and data recording, for each successive 15-minute period.

(e) Unless otherwise approved by the department, minimum procedures for COMS shall include a method for producing a simulated zero opacity condition and an upscale (high-level) opacity condition using a certified neutral density filter or other related technique to produce a known obscuration of the light beam. Procedures shall provide a system check of all the analyzer's internal optical surfaces and all electronic circuitry, including the lamp and photodetector assembly normally used in the measurement of opacity.

(f) The owner or operator of a CMS installed in accordance with the provisions of 40 CFR part 63 and the applicable CMS performance specifications shall check the zero (low-level) and high-level calibration drifts at least once daily in accordance with the written procedure specified in the performance evaluation plan developed under sub. (5) (c) 1. and 2. The zero (low-level) and high-level calibration drifts shall be adjusted, at a minimum, whenever the 24-hour zero (low-level) drift exceeds 2 times the limits of the applicable performance specifications specified in the relevant standard. The system shall allow the amount of excess zero (low-level) and high-level drift measured at the 24-hour interval checks to be recorded and quantified, whenever specified. For COMS, all optical and instrumental surfaces exposed to the effluent gases shall be cleaned prior to performing the zero (low-level) and high-level drift adjustments; the optical surfaces and instrumental surfaces shall be cleaned when the cumulative automatic zero compensation, if applicable, exceeds 4% opacity.

(g) 1. A CMS is out of control if any of the following occurs:

a. The zero (low-level), mid-level, if applicable, or high-level calibration drift exceeds 2 times the applicable calibration drift specification in the applicable performance specification or in the relevant standard.

b. The CMS fails a performance test audit, including a cylinder gas audit, relative accuracy audit, relative accuracy test audit or linearity test audit.

c. The COMS calibration drift exceeds 2 times the limit in the applicable performance specification in the relevant standard.

2. When the CMS is out of control, the owner or operator of the affected source shall take the necessary corrective action and shall repeat all necessary tests which indicate that the system is out of control. The owner or operator shall take corrective action and conduct retesting until the performance requirements are below the applicable limits. The beginning of the out-of-control period is the hour the owner or operator conducts a performance check, such as calibration drift, that indicates an exceedance of the performance requirements established under 40 CFR part 63. The end of the out-of-control period is the hour following the completion of corrective action and successful demonstration that the system is within the allowable limits. During the period the CMS is out of control, recorded data may not be used in data averages and calculations or to meet any data availability requirement established under 40 CFR part 63 and in chs. NR 460 to 469.

(h) The owner or operator of a CMS that is out of control as defined in par. (g) shall submit all information concerning out-of-control periods, including start and end dates and hours and descriptions of corrective actions taken, in the excess emissions and continuous monitoring system performance report required in s. NR 460.09 (5) (c).

(4) QUALITY CONTROL PROGRAM. (a) The results of the quality control program required in this subsection shall be considered by the department when it determines the validity of monitoring data.

(b) The owner or operator of an affected source that is required to use a CMS and is subject to the monitoring requirements of this section and a relevant standard shall develop and implement a CMS quality control program. As part of the quality control program, the owner or operator shall develop and submit to the department for approval upon request a site-specific performance evaluation test plan for the CMS performance evaluation required in sub. (5) (c) 1., according to the procedures specified in sub. (5). In addition, each quality control program shall include, at a minimum, a written protocol that describes procedures for each of the following operations:

1. Initial and any subsequent calibration of the CMS.
2. Determination and adjustment of the calibration drift of the CMS.
3. Preventive maintenance of the CMS, including spare parts inventory.
4. Data recording, calculations, and reporting.
5. Accuracy audit procedures, including sampling and analysis methods.
6. Program of corrective action for a malfunctioning CMS.

(c) The owner or operator shall keep the written procedures required by par. (b) on record for the life of the affected source or until the affected source is no longer subject to the provisions of 40 CFR part 63 or chs. NR 460 to 469, to be made available for inspection, upon request, by the department. If the performance evaluation plan is revised, the owner or operator shall keep previous versions of the performance evaluation plan on record to be made available for inspection, upon request, by the department, for a period of 5 years after each revision to the plan. Where relevant, these written procedures may be incorporated as part of the affected source's startup, shutdown and malfunction plan to avoid duplication of planning and recordkeeping efforts.

(5) PERFORMANCE EVALUATION OF CONTINUOUS MONITORING SYSTEMS. (a) *General.* When required by a relevant standard, and at any other time as may be required under section 114 of the act (42 USC 7414), the owner or operator of an affected source being monitored shall conduct a performance evaluation of the CMS. The performance evaluation shall be conducted according to the applicable specifications and procedures described in this section or in the relevant standard.

(b) *Notification of performance evaluation.* The owner or operator shall notify the department in writing of the date of the



performance evaluation simultaneously with the notification of the performance test date required under s. NR 460.06 (2) or at least 30 days prior to the date the performance evaluation is scheduled to begin if no performance test is required.

(c) *Submission of site-specific performance evaluation test plan.* 1. Before conducting a required CMS performance evaluation, the owner or operator of an affected source shall develop and submit a site-specific performance evaluation test plan to the department for approval upon request. The performance evaluation test plan shall include the evaluation program objectives, an evaluation program summary, the performance evaluation schedule, data quality objectives, and both an internal and external quality assurance program. Data quality objectives are the pre-evaluation expectations of precision, accuracy, and completeness of data.

2. The internal quality assurance program shall include, at a minimum, the activities planned by routine operators and analysts to provide an assessment of CMS performance. The external quality assurance program shall include, at a minimum, systems audits that include the opportunity for on-site evaluation by the department of instrument calibration, data validation, sample logging and documentation of quality control data and field maintenance activities.

3. The owner or operator of an affected source shall submit the site-specific performance evaluation test plan to the department at least 30 days before the performance test or performance evaluation is scheduled to begin, or on a mutually agreed upon date, and review and approval of the performance evaluation test plan by the department shall occur with the review and approval of the site-specific test plan under s. NR 460.06 (2).

4. The department may request additional relevant information after the submittal of a site-specific performance evaluation test plan.

5. In the event that the department fails to approve or disapprove the site-specific performance evaluation test plan within the time period specified under s. NR 460.06 (2), the following conditions shall apply:

a. If the owner or operator intends to demonstrate compliance using the monitoring methods specified in the relevant standard, the owner or operator shall conduct the performance evaluation within the time specified in this chapter using the specified methods.

b. If the owner or operator intends to demonstrate compliance by using an alternative to a monitoring method specified in the relevant standard, the owner or operator shall refrain from conducting the performance evaluation until the department approves the use of the alternative method. If the department does not approve the use of the alternative method within 5 days before the performance evaluation is scheduled to begin, the performance evaluation deadlines specified in par. (d) may be extended such that the owner or operator shall conduct the performance evaluation within 60 calendar days after the department approves the use of the alternative method.

c. Notwithstanding the requirements in subd. 5. b., the owner or operator may proceed to conduct the performance evaluation as required in this section, without the department's prior approval of the site-specific performance evaluation test plan, if the specified monitoring methods is subsequently chosen instead of an alternative.

6. Neither the submission of a site-specific performance evaluation test plan for approval, nor the department's approval or disapproval of a plan, nor the department's failure to approve or disapprove a plan in a timely manner shall cause any of the following:

a. Relieve an owner or operator of legal responsibility for compliance with any applicable provisions of 40 CFR part 63, chs. NR 460 to 469 or with any other applicable federal, state or local requirement.

b. Prevent the department from implementing or enforcing 40 CFR part 63, chs. NR 460 to 469 or taking any other action under the act.

(d) *Conduct of performance evaluation and performance evaluation dates.* The owner or operator of an affected source shall conduct a performance evaluation of a required CMS during any performance test required under s. NR 460.06 in accordance with the applicable performance specification as specified in the relevant standard. If the owner or operator of an affected source elects to submit COMS data for compliance with a relevant opacity emission standard as provided under s. NR 460.05(6)(f), a performance evaluation shall be conducted of the COMS as specified in the relevant standard, before the performance test required under s. NR 460.06 is conducted, in time to submit the results of the performance evaluation as specified in par. (e) 2. If a performance test is not required, or the requirement for a performance test has been waived under s. NR 460.06 (7), the owner or operator of an affected source shall conduct the performance evaluation not later than 180 days after the appropriate compliance date for the affected source, as specified in s. NR 460.06 (1), or as otherwise specified in the relevant standard.

(e) *Reporting performance evaluation results.* 1. The owner or operator shall furnish the department a copy of a written report of the results of the performance evaluation simultaneously with the results of the performance test required under s. NR 460.06, or within 60 days of completion of the performance evaluation if no test is required, unless otherwise specified in a relevant standard. The department may request that the owner or operator submit the raw data from a performance evaluation in the report of the performance evaluation results.

2. The owner or operator of an affected source using a COMS to determine opacity compliance during any performance test required under s. NR 460.06 shall furnish the department 2 or, upon request, 3 copies of a written report of the results of the COMS performance evaluation under this subsection. The copies shall be provided at least 15 calendar days before the performance test required under s. NR 460.06 is conducted.

(6) *USE OF AN ALTERNATIVE MONITORING METHOD.* (a) *Alternatives.* After receipt and consideration of written application, the department may approve alternatives to any monitoring methods or procedures of 40 CFR part 63 or chs. NR 460 to 469 including, but not limited to, any of the following:

1. Alternative monitoring requirements when installation of a CMS specified by a relevant standard would not provide accurate measurements due to liquid water or other interferences caused by substances within the effluent gases.

2. Alternative monitoring requirements when the affected source is infrequently operated.

3. Alternative monitoring requirements to accommodate CEMS that require additional measurements to correct for stack moisture conditions.

4. Alternative locations for installing CMS when the owner or operator can demonstrate that installation at alternate locations will enable accurate and representative measurements.

5. Alternate methods for converting pollutant concentration measurements to units of the relevant standard.

6. Alternate procedures for performing daily checks of zero (low-level) and high-level drift that do not involve use of high-level gases or test cells.

7. Alternatives to the american society for testing and materials test methods or sampling procedures specified by any relevant standard.

8. Alternative CMS that do not meet the design or performance requirements in 40 CFR part 63 or chs. NR 460 to 469, but adequately demonstrate a definite and consistent relationship between their measurements and the measurements of opacity by a system complying with the requirements as specified in the rele-

vant standard. The department may require that the demonstration be performed for each affected source.

9. Alternative monitoring requirements when the effluent from a single affected source or the combined effluent from 2 or more affected sources is released to the atmosphere through more than one point.

(b) *Disputed results.* If the department finds reasonable grounds to dispute the results obtained by an alternative monitoring method, requirement or procedure, the department may require the use of a method, requirement or procedure specified in this section or in the relevant standard. If the results of the specified and alternative method, requirement or procedure do not agree, the results obtained by the specified method, requirement or procedure shall prevail.

(c) *Request to use alternative monitoring method.* 1. An owner or operator who wishes to use an alternative monitoring method shall submit an application to the department as described in subd. 2. The application may be submitted at any time provided that the monitoring method is not used to demonstrate compliance with a relevant standard or other requirement. If the alternative monitoring method is to be used to demonstrate compliance with a relevant standard, the application shall be submitted not later than with the site-specific test plan required under s. NR 460.06 (2) or with the site-specific performance evaluation plan or at least 60 days before the performance evaluation is scheduled to begin.

2. The application shall contain a description of the proposed alternative monitoring system and a performance evaluation test plan, if required, as specified in sub. (5) (c). In addition, the application shall include information justifying the owner or operator's request for an alternative monitoring method, such as the technical or economic infeasibility, or the impracticality, of the affected source using the required method.

3. The owner or operator may submit the information required in this subsection well in advance of the submittal dates specified in subd. 1. to ensure a timely review by the department in order to meet the compliance demonstration date specified in this section or the relevant standard.

(d) *Approval of request to use alternative monitoring method.* 1. The department shall notify the owner or operator of approval or intention to deny approval of the request to use an alternative monitoring method within 30 calendar days after receipt of the original request and within 30 calendar days after receipt of any supplementary information that is submitted. Before disapproving any request to use an alternative monitoring method, the department shall notify the applicant of the department's intention to disapprove the request together with all of the following:

a. Notice of the information and findings on which the intended disapproval is based.

b. Notice of opportunity for the owner or operator to present additional information to the department before final action on the request. At the time the department notifies the applicant of its intention to disapprove the request, the department shall specify how much time the owner or operator will have after being notified of the intended disapproval to submit the additional information.

2. The department may establish general procedures and criteria in a relevant standard to accomplish the requirements of subd. 1.

3. If the department approves the use of an alternative monitoring method for an affected source under subd. 1., the owner or operator of the source shall continue to use the alternative monitoring method until he or she receives approval from the department to use another monitoring method as allowed under this subsection.

(e) *Alternative to the relative accuracy test.* An alternative to the relative accuracy test for CEMS specified in a relevant standard may be requested as follows:

1. An alternative to the test method for determining relative accuracy is available for affected sources with emission rates demonstrated to be less than 50% of the relevant standard. The owner or operator of an affected source may petition the department under subd. 2. to substitute the relative accuracy test in section 7 of Performance Specification 2 in Appendix B of 40 CFR part 60, incorporated by reference in s. NR 484.04, with the procedures in section 10 if the results of a performance test conducted according to the requirements in s. NR 460.06, or other tests performed following the criteria in s. NR 460.06, demonstrate that the emission rate of the pollutant of interest in the units of the relevant standard is less than 50% of the relevant standard. For affected sources subject to emission limitations expressed as control efficiency levels, the owner or operator may petition the department to substitute the relative accuracy test with the procedures in section 10 of Performance Specification 2 if the control device exhaust emission rate is less than 50% of the level needed to meet the control efficiency requirement. The alternative procedures do not apply if the CEMS is used continuously to determine compliance with the relevant standard.

2. The petition to use an alternative to the relative accuracy test shall include a detailed description of the procedures to be applied, the location and the procedure for conducting the alternative, the concentration or response levels of the alternative relative accuracy materials, and the other equipment checks included in the alternative procedures. The department shall review the petition for completeness and applicability. The department's determination to approve an alternative shall depend on the intended use of the CEMS data and may require specifications more stringent than in Performance Specification 2.

3. The department shall review the permission to use an alternative to the CEMS relative accuracy test and may rescind the permission if the CEMS data from a successful completion of the alternative relative accuracy procedure indicate that the affected source's emissions are approaching the level of the relevant standard. The criterion for reviewing the permission is that the collection of CEMS data shows that emissions have exceeded 70% of the relevant standard for any averaging period, as specified in the relevant standard. For affected sources subject to emission limitations expressed as control efficiency levels, the criterion for reviewing the permission is that the collection of CEMS data shows that exhaust emissions have exceeded 70% of the level needed to meet the control efficiency requirement for any averaging period, as specified in the relevant standard. The owner or operator of the affected source shall maintain records and determine the level of emissions relative to the criterion for permission to use an alternative for relative accuracy testing. If this criterion is exceeded, the owner or operator shall notify the department within 10 days of the occurrence and include a description of the nature and cause of the increased emissions. The department shall review the notification and may rescind permission to use an alternative and require the owner or operator to conduct a relative accuracy test of the CEMS as specified in section 7 of Performance Specification 2 in Appendix B of 40 CFR part 60, incorporated by reference in s. NR 484.04.

(7) **REDUCTION OF MONITORING DATA.** (a) The owner or operator of each CMS shall reduce the monitoring data as specified in this subsection. In addition, each relevant standard may contain additional requirements for reducing monitoring data. When additional requirements are specified in a relevant standard, the standard will identify any unnecessary or duplicated requirements in this subsection that the owner or operator need not comply with.

(b) The owner or operator of each COMS shall reduce all data to 6-minute averages calculated from 36 or more data points equally spaced over each 6-minute period. Data from CEMS for measurement other than opacity, unless otherwise specified in the relevant standard, shall be reduced to 1-hour averages computed from 4 or more data points equally spaced over each 1-hour period, except during periods when calibration, quality assurance

or maintenance activities pursuant to provisions of 40 CFR part 63 or chs. NR 460 to 469 are being performed. During these periods, a valid hourly average shall consist of at least 2 data points with each representing a 15-minute period. Alternatively, an arithmetic or integrated 1-hour average of CEMS data may be used. Time periods for averaging are defined in s. NR 460.02.

(c) The data may be recorded in reduced or nonreduced form.

(d) All emission data shall be converted into units of the relevant standard for reporting purposes using the conversion procedures specified in that standard. After conversion into units of the relevant standard, the data may be rounded to the same number of significant digits as used in that standard to specify the emission limit.

(e) Monitoring data recorded during periods of unavoidable CMS breakdowns, out-of-control periods, repairs, maintenance periods, calibration checks and zero (low-level) and high-level adjustments may not be included in any data average computed under 40 CFR part 63 or under chs. NR 460 to 469.

**History:** Cr. Register, March, 1997, No. 495, eff. 4-1-97.

**NR 460.08 Notification requirements. (1) APPLICABILITY AND GENERAL INFORMATION.** (a) The requirements in this section apply to owners and operators of affected sources that are subject to the provisions of 40 CFR part 63 and chs. NR 460 to 469, unless specified otherwise in a relevant standard.

(b) For affected sources that have been granted an extension of compliance under Subpart D of 40 CFR part 63, the requirements of this section do not apply to those sources while they are operating under compliance extensions.

**(2) INITIAL NOTIFICATIONS.** (a) 1. The requirements of this subsection apply to the owner or operator of an affected source when the source becomes subject to a relevant standard.

2. If an area source that otherwise would be subject to an emission standard or other requirement established under 40 CFR part 63 or chs. NR 460 to 469 if it were a major source subsequently increases its emissions of hazardous air pollutants, or its potential to emit hazardous air pollutants, such that the source is a major source that is subject to the emission standard or other requirement, the source shall be subject to the notification requirements of this section.

3. Affected sources that are required under this subsection to submit an initial notification may use the application for approval of construction or reconstruction under ch. NR 406, if relevant, to fulfill the initial notification requirements of this subsection.

(b) The owner or operator of an affected source that has an initial startup before the effective date of a relevant standard under 40 CFR part 63 shall notify the department in writing that the source is subject to the relevant standard. The notification, which shall be submitted not later than 120 calendar days after the effective date of the relevant standard, or within 120 calendar days after the source becomes subject to the relevant standard, shall provide all of the following information:

1. The name and address of the owner or operator.
2. The address where the affected source is located.
3. An identification of the relevant standard, or other requirement, that is the basis of the notification and the source's compliance date.
4. A brief description of the nature, size, design and method of operation of the source, including its operating design capacity and an identification of each point of emission for each hazardous air pollutant, or if a definitive identification is not yet possible, a preliminary identification of each point of emission for each hazardous air pollutant.
5. A statement of whether the affected source is a major source or an area source.

(c) The owner or operator of a new or reconstructed affected source, or a source that has been reconstructed such that it is an affected source, that has an initial startup after the effective date

of a relevant standard under 40 CFR part 63 and for which an application for approval of construction or reconstruction is not required under ch. NR 406, shall notify the department in writing that the source is subject to the relevant standard no later than 120 days after initial startup. The notification shall provide all the information required in par. (b) 1. to 5., delivered or postmarked with the notification required in par. (e).

(d) The owner or operator of a new or reconstructed major affected source that has an initial startup after the effective date of a relevant standard under 40 CFR part 63 and for which an application for approval of construction or reconstruction is required under ch. NR 406 shall provide all of the following information in writing to the department:

1. A notification of intention to construct a new major affected source, reconstruct a major affected source or reconstruct a major source such that the source becomes a major affected source with the application for approval of construction or reconstruction.

2. A notification of the date when construction or reconstruction was commenced, submitted simultaneously with the application for approval of construction or reconstruction, if construction or reconstruction was commenced before the effective date of the relevant standard.

3. A notification of the date when construction or reconstruction was commenced, delivered or postmarked not later than 30 days after the date, if construction or reconstruction was commenced after the effective date of the relevant standard.

4. A notification of the anticipated date of startup of the source, delivered or postmarked not more than 60 days nor less than 30 days before the date.

5. A notification of the actual date of startup of the source, delivered or postmarked within 15 calendar days after that date.

(e) After the effective date of any relevant standard established under 40 CFR part 63, an owner or operator who intends to construct a new affected source or reconstruct an affected source subject to the standard, or reconstruct a source such that it becomes an affected source subject to the standard, shall notify the department, in writing, of the intended construction or reconstruction. The notification shall be submitted as soon as practicable before the construction or reconstruction is planned to commence, but no sooner than the effective date of the relevant standard, if the construction or reconstruction commences after the effective date of a relevant standard promulgated in 40 CFR part 63. The notification shall be submitted as soon as practicable before startup but no later than 60 days after the effective date of a relevant standard promulgated in 40 CFR part 63 if the construction or reconstruction had commenced and initial startup had not occurred before the standard's effective date. The notification shall include all the information required for an application for approval of construction or reconstruction as specified in ch. NR 406. For major sources, the application for approval of construction or reconstruction may be used to fulfill the requirements of this subsection.

**(3) REQUEST FOR A COMPLIANCE DATE EXTENSION.** If the owner or operator of an affected source cannot comply with a relevant standard by the applicable compliance date for that source, or if the owner or operator has installed BACT or technology to meet LAER consistent with s. NR 460.05 (7) (d), the owner or operator may submit to the department a request for an extension of the compliance date as specified in s. NR 460.05 (7) (c) to (em).

**(4) NOTIFICATION THAT SOURCE IS SUBJECT TO SPECIAL COMPLIANCE REQUIREMENTS.** An owner or operator of a new MACT source that is subject to special compliance requirements as specified in s. NR 460.05 (2) (c) and (d) shall notify the department of the compliance obligations not later than the notification dates established in sub. (2) for new MACT sources that are not subject to the special provisions.

**(5) NOTIFICATION OF PERFORMANCE TEST.** The owner or operator of an affected source shall notify the department in writing of



his or her intention to conduct a performance test at least 30 calendar days before the performance test is scheduled to begin to allow the department to review and approve the site-specific test plan required under s. NR 460.06 (2) and to have an observer present during the test.

**(6) NOTIFICATION OF OPACITY AND VISIBLE EMISSION OBSERVATIONS.** The owner or operator of an affected source shall notify the department in writing of the anticipated date for conducting the opacity or visible emission observations specified in s. NR 460.05 (6) (d), if the observations are required for the source by a relevant standard. The notification shall be submitted with the notification of the performance test date, as specified in sub. (5), or if no performance test is required or visibility or other conditions prevent the opacity or visible emission observations from being conducted concurrently with the initial performance test required under s. NR 460.06, the owner or operator shall deliver or postmark the notification not less than 30 days before the opacity or visible emission observations are scheduled to take place.

**(7) ADDITIONAL NOTIFICATION REQUIREMENTS FOR SOURCES WITH CONTINUOUS MONITORING SYSTEMS.** The owner or operator of an affected source required to use a continuous monitoring system by a relevant standard shall furnish the department written notification of all of the following:

(a) A notification of the date the continuous monitoring system performance evaluation under s. NR 460.07 (5) is scheduled to begin, submitted simultaneously with the notification of the performance test date required under s. NR 460.06 (2). If no performance test is required, or if the requirement to conduct a performance test has been waived for an affected source under s. NR 460.06 (7), the owner or operator shall notify the department in writing of the date of the performance evaluation at least 30 calendar days before the evaluation is scheduled to begin.

(b) A notification that continuous opacity monitoring system data results will be used to determine compliance with the applicable opacity emission standard during a performance test required by s. NR 460.06 in lieu of Method 9 or other opacity emissions test method data, as allowed by s. NR 460.05 (6) (f) 2., if compliance with an opacity emission standard is required for the source by a relevant standard. The notification shall be submitted at least 30 calendar days before the performance test is scheduled to begin.

(c) A notification that the criterion necessary to continue use of an alternative to relative accuracy testing, as provided by s. NR 460.07 (6) (e), has been exceeded. The notification shall be delivered or postmarked not later than 10 days after the occurrence of the exceedance, and it shall include a description of the nature and cause of the increased emissions.

**(8) NOTIFICATION OF COMPLIANCE STATUS.** (a) The requirements of pars. (b) and (c) apply when an affected source becomes subject to a relevant standard.

(b) 1. Before a part 70 permit has been issued to the owner or operator of an affected source, and each time a notification of compliance status is required under 40 CFR part 63 or chs. NR 460 to 469, the owner or operator of the source shall submit to the department a notification of compliance status, signed by the responsible official who shall certify its accuracy, attesting to whether the source has complied with the relevant standard. The notification shall list all of the following:

a. The methods that were used to determine compliance.

b. The results of any performance tests, opacity or visible emission observations, continuous monitoring system performance evaluations, and other monitoring procedures or methods that were conducted.

c. The methods that will be used for determining continuing compliance, including a description of monitoring and reporting requirements and test methods.

d. The type and quantity of hazardous air pollutants emitted by the source, or surrogate pollutants if specified in the relevant

standard, reported in units and averaging times and in accordance with the test methods specified in the relevant standard.

e. An analysis demonstrating whether the affected source is a major source or an area source, using the emissions data generated for this notification.

f. A description of the air pollution control equipment or method for each emission point, including each control device or method for each hazardous air pollutant and the control efficiency (percent) for each control device or method.

g. A statement by the owner or operator of the affected existing, new or reconstructed source as to whether the source has complied with the relevant standard or other requirements.

2. The notification shall be sent before the close of business on the 60th day following the completion of the relevant compliance demonstration activity specified in the relevant standard, unless a different reporting period is specified in a relevant standard, in which case the letter shall be sent before the close of business on the day the report of the relevant testing or monitoring results is required to be delivered or postmarked. If no performance test is required but opacity or visible emission observations are required to demonstrate compliance with an opacity or visible emission standard under 40 CFR part 63 or chs. NR 460 to 469, the notification of compliance status shall be sent before close of business on the 30th day following the completion of opacity or visible emission observations.

(c) After a part 70 permit has been issued to the owner or operator of an affected source, the owner or operator of the source shall comply with all requirements for compliance status reports contained in the source's part 70 permit, including reports required under 40 CFR part 63 or chs. NR 460 to 469. After a part 70 permit has been issued to the owner or operator of an affected source, and each time a notification of compliance status is required under 40 CFR part 63 or chs. NR 460 to 469, the owner or operator of the source shall submit the notification of compliance status to the department following completion of the relevant compliance demonstration activity specified in the relevant standard.

(d) If an owner or operator of an affected source submits estimates or preliminary information in the application for approval of construction or reconstruction required in ch. NR 406 in place of the actual emissions data or control efficiencies, the owner or operator shall submit the actual emissions data and other correct information as soon as available but no later than with the initial notification of compliance status required in this section.

(e) Advice on a notification of compliance status may be obtained from the department.

**(9) ADJUSTMENT TO TIME PERIODS OR POSTMARK DEADLINES FOR SUBMITTAL AND REVIEW OF REQUIRED COMMUNICATIONS.** (a) An owner or operator shall request the adjustment provided for in pars. (b) and (c) each time he or she wishes to change an applicable time period or postmark deadline specified in chs. NR 460 to 469 or in 40 CFR part 63.

(b) Notwithstanding time periods or postmark deadlines specified in chs. NR 460 to 469 or 40 CFR part 63 for the submittal of information to the department by an owner or operator, or the review of the information by the department, time periods or deadlines may be changed by mutual agreement between the owner or operator and the department. An owner or operator who wishes to request a change in a time period or postmark deadline for a particular requirement shall request the adjustment in writing as soon as practicable before the subject activity is required to take place. The owner or operator shall include in the request whatever information he or she considers useful to convince the department that an adjustment is warranted.

(c) If, in the department's judgment, an owner or operator's request for an adjustment to a particular time period or postmark deadline is warranted, the department shall approve the adjustment. The department shall notify the owner or operator in writing of approval or disapproval of the request for an adjustment within

15 calendar days of receiving sufficient information to evaluate the request.

(d) If the department is unable to meet a specified deadline, it shall notify the owner or operator of any significant delay and inform the owner or operator of the amended schedule.

**(10) CHANGE IN INFORMATION ALREADY PROVIDED.** Any change in the information already provided under this section shall be provided to the department in writing within 15 calendar days after the change.

**History:** Cr. Register, March, 1997, No. 495, eff. 4-1-97.

**NR 460.09 Recordkeeping and reporting requirements.** **(1) APPLICABILITY AND GENERAL INFORMATION.** (a) The requirements of this section apply to owners or operators of affected sources who are subject to the provisions of 40 CFR part 63 or chs. NR 460 to 469, unless specified otherwise in a relevant standard.

(b) For affected sources that have been granted an extension of compliance under Subpart D of 40 CFR part 63, the requirements of this section do not apply to those sources while they are operating under compliance extensions.

(c) The owner or operator of an affected source subject to recordkeeping and reporting requirements established under 40 CFR part 63 or chs. NR 460 to 469 shall submit the required reports to the department.

(d) If an owner or operator supervises one or more stationary sources in Wisconsin affected by more than one standard established pursuant to section 112 of the act (42 USC 7412), the owner or operator and the department may arrange by mutual agreement a common schedule on which periodic reports required for each source shall be submitted throughout the year. The allowance in the previous sentence applies beginning one year after the latest compliance date for any relevant standard established pursuant to section 112 of the act (42 USC 7412). Procedures governing the implementation of this provision are specified in s. NR 460.08 (9).

(e) If an owner or operator supervises one or more stationary sources affected by standards established pursuant to section 112 of the act (42 USC 7412), as amended November 15, 1990, and standards set under 40 CFR part 60, 40 CFR part 61, or both parts, the owner or operator and the department may arrange by mutual agreement a common schedule on which periodic reports required by each relevant standard shall be submitted throughout the year. The allowance in the previous sentence applies beginning one year after the stationary source is required to be in compliance with the relevant section 112 standard, or one year after the stationary source is required to be in compliance with the applicable 40 CFR part 60 or 40 CFR part 61 standard, whichever is latest. Procedures governing the implementation of this provision are specified in s. NR 460.08 (9).

**(2) GENERAL RECORDKEEPING REQUIREMENTS.** (a) The owner or operator of an affected source subject to the provisions of 40 CFR part 63 or chs. NR 460 to 469 shall maintain files of all information, including all reports and notifications, required by 40 CFR part 63 or chs. NR 460 to 469 recorded in a form suitable and readily available for expeditious inspection and review. The files shall be retained for at least 5 years following the date of each occurrence, measurement, maintenance, corrective action, report or record. At a minimum, the most recent 2 years of data shall be retained on site. The remaining 3 years of data may be retained off site. Files may be maintained on microfilm, on a computer, on computer floppy disks, on magnetic tape disks or on microfiche.

(b) The owner or operator of an affected source subject to the provisions of 40 CFR part 63 shall maintain relevant records for the source of all of the following:

1. The occurrence and duration of each startup, shutdown or malfunction of the process equipment.

2. The occurrence and duration of each malfunction of the air pollution control equipment.

3. All maintenance performed on the air pollution control equipment.

4. Actions taken during periods of startup, shutdown and malfunction, including corrective actions to restore malfunctioning process and air pollution control equipment to its normal or usual manner of operation, when actions are different from the procedures specified in the affected source's startup, shutdown and malfunction plan, required in s. NR 460.05 (4) (c).

5. All information necessary to demonstrate conformance with the affected source's startup, shutdown and malfunction plan, required in s. NR 460.05 (4) (c), when all actions taken during periods of startup, shutdown and malfunction, including corrective actions to restore malfunctioning process and air pollution control equipment to its normal or usual manner of operation, are consistent with the procedures specified in the plan. The information needed to demonstrate conformance with the startup, shutdown and malfunction plan may be recorded using a checklist, or some other effective form of recordkeeping, in order to minimize the recordkeeping burden for conforming events.

6. Each period during which a continuous monitoring system is malfunctioning or inoperative, including out-of-control periods.

7. All required measurements needed to demonstrate compliance with a relevant standard, including, but not limited to, 15-minute averages of continuous monitoring system data, raw performance testing measurements and raw performance evaluation measurements, that support data that the source is required to report.

8. All results of performance tests, continuous monitoring system performance evaluations, and opacity and visible emission observations.

9. All measurements as may be necessary to determine the conditions of performance tests and performance evaluations.

10. All continuous monitoring system calibration checks.

11. All adjustments and maintenance performed on continuous monitoring systems.

12. Any information demonstrating whether a source is meeting the requirements for a waiver of recordkeeping or reporting requirements under 40 CFR part 63 or chs. NR 460 to 469, if the source has been granted a waiver under sub. (6).

13. All emission levels relative to the criterion for obtaining permission to use an alternative to the relative accuracy test, if the source has been granted permission under s. NR 460.07 (6) (e).

14. All documentation supporting initial notifications and notifications of compliance status under s. NR 460.08.

(c) If an owner or operator determines that his or her stationary source that emits, or has the potential to emit, without considering controls, one or more hazardous air pollutants is not subject to a relevant standard or other requirement established under 40 CFR part 63 or chs. NR 460 to 469, the owner or operator shall keep a record of the applicability determination on site at the source for a period of 5 years after the determination, or until the source changes its operations to become an affected source, whichever comes first. The record of the applicability determination shall include an analysis or other information that demonstrates why the owner or operator believes the source is not an affected source. The source might be an area source, for example. The analysis or other information shall be sufficiently detailed to allow the department to make a finding about the source's applicability status with regard to the relevant standard or other requirement. If relevant, the analysis shall be performed in accordance with requirements established in subparts of 40 CFR part 63 for this purpose for particular categories of stationary sources. If relevant, the analysis should be performed in accordance with EPA guidance materials

published to assist sources in making applicability determinations under section 112 of the act (42 USC 7412), if any.

**(3) ADDITIONAL RECORDKEEPING REQUIREMENTS FOR SOURCES WITH CONTINUOUS MONITORING SYSTEMS.** (a) In addition to complying with the requirements specified in sub. (2) (a) and (b), the owner or operator of an affected source required to install a continuous monitoring system by a relevant standard shall maintain records for the source of all of the following:

1. All required continuous monitoring system measurements, including monitoring data recorded during unavoidable continuous monitoring system breakdowns and out-of-control periods.
2. The date and time identifying each period during which the continuous monitoring system was inoperative except for zero (low-level) and high-level checks.
3. The date and time identifying each period during which the continuous monitoring system was out of control, as defined in s. NR 460.07 (3) (g).
4. The specific identification, including date and times, of each period of excess emissions and parameter monitoring exceedances, as defined in the relevant standards, that occurs during startups, shutdowns and malfunctions of the affected source.
5. The specific identification, including the date and times, of each period of excess emissions and parameter monitoring exceedances, as defined in the relevant standards, that occurs during periods other than startups, shutdowns and malfunctions of the affected source.
6. The nature and cause of any malfunction, if known.
7. The corrective action taken or preventive measures adopted.
8. The nature of the repairs or adjustments to the continuous monitoring system that was inoperative or out of control.
9. The total process operating time during the reporting period.
10. All procedures that are part of a quality control program developed and implemented for the continuous monitoring system under s. NR 460.07 (4).

(b) In order to satisfy the requirements of par. (a) 6. to 8. and to avoid duplicative recordkeeping efforts, the owner or operator may use the affected source's startup, shutdown and malfunction plan or records kept to satisfy the recordkeeping requirements of the startup, shutdown and malfunction plan specified in s. NR 460.05 (4), provided that the plan and records adequately address the requirements of par. (a) 6. to 8.

**(4) GENERAL REPORTING REQUIREMENTS.** (a) *General.* Notwithstanding the requirements in this subsection or sub. (5), the owner or operator of an affected source subject to reporting requirements under 40 CFR part 63 or under chs. NR 460 to 469 shall submit reports to the department in accordance with the reporting requirements in the relevant standards.

(b) *Reporting results of performance tests.* The owner or operator of an affected source shall report the results of any performance test under s. NR 460.06 to the department. The owner or operator of an affected source shall report the results of the performance test to the department before the close of business on the 60th day following the completion of the performance test, unless specified otherwise in a relevant standard or as approved otherwise in writing by the department. The results of the performance test shall be submitted as part of the notification of compliance status required under s. NR 460.08 (8).

(c) *Reporting results of opacity or visible emission observations.* The owner or operator of an affected source required to conduct opacity or visible emission observations by a relevant standard shall report the opacity or visible emission results, produced using Method 9 or Method 22 in Appendix A of 40 CFR part 60, incorporated by reference in s. NR 484.04, or an alternative to these test methods, along with the results of the performance test

required under s. NR 460.06. If no performance test is required, or if visibility or other conditions prevent the opacity or visible emission observations from being conducted concurrently with the performance test required under s. NR 460.06, the owner or operator shall report the opacity or visible emission results before the close of business on the 30th day following the completion of the opacity or visible emission observations.

(d) *Progress reports.* The owner or operator of an affected source who is required to submit progress reports as a condition of receiving a compliance date extension under s. NR 460.05 (7) shall submit the reports to the department by the dates specified in the written compliance date extension.

(e) *Startup, shutdown and malfunction reports.* 1. Periodic reports. If actions taken by an owner or operator during a startup, shutdown or malfunction of an affected source, including actions taken to correct a malfunction, are consistent with the procedures specified in the source's startup, shutdown and malfunction plan, the owner or operator shall state the information in a startup, shutdown and malfunction report. Reports shall only be required if a startup, shutdown or malfunction occurred during the reporting period. The startup, shutdown and malfunction report shall consist of a letter, containing the name, title and signature of the owner or operator or other responsible official who is certifying its accuracy, that shall be submitted to the department semiannually, or on a more frequent basis if specified otherwise in a relevant standard or as established otherwise in the source's part 70 permit. The startup, shutdown and malfunction report shall be delivered or postmarked by the 30th day following the end of each calendar half, or other calendar reporting period, as appropriate. If the owner or operator is required to submit excess emissions and continuous monitoring system performance, or other periodic, reports under 40 CFR part 63 or chs. NR 460 to 469, the startup, shutdown and malfunction reports required under this subsection may be submitted simultaneously with the excess emissions and continuous monitoring system performance or other reports. If startup, shutdown and malfunction reports are submitted with excess emissions and continuous monitoring system performance or other periodic reports, and the owner or operator receives approval to reduce the frequency of reporting for the latter under sub. (5), the frequency of reporting for the startup, shutdown and malfunction reports also may be reduced if the department does not object to the intended change. The procedures to implement this reduced frequency of reporting shall be the same as the procedures specified in sub. (5) (c).

2. Immediate reports. Notwithstanding the allowance to reduce the frequency of reporting for periodic startup, shutdown and malfunction reports under subd. 1., any time an action taken by an owner or operator during a startup, shutdown or malfunction, including actions taken to correct a malfunction, is not consistent with the procedures specified in the affected source's startup, shutdown and malfunction plan, the owner or operator shall report the actions taken for that event within 2 working days after commencing actions inconsistent with the plan followed by a letter within 7 working days after the end of the event. The immediate report required under this subdivision shall consist of a telephone call or facsimile transmission to the department within 2 working days after commencing actions inconsistent with the plan, and it shall be followed by a letter, delivered or postmarked within 7 working days after the end of the event, that contains the name, title, and signature of the owner or operator or other responsible official who is certifying its accuracy, explaining the circumstances of the event, the reasons for not following the startup, shutdown and malfunction plan, and whether any excess emissions or parameter monitoring exceedances or both are believed to have occurred.

3. Alternative reporting arrangements. Notwithstanding the requirements of subd. 2., the owner or operator may make alternative reporting arrangements, in advance, with the department.



Procedures governing the arrangement of alternative reporting requirements under this subsection are specified in s. NR 460.08 (9).

(5) **ADDITIONAL REPORTING REQUIREMENTS FOR SOURCES WITH CONTINUOUS MONITORING SYSTEMS.** (a) *General.* When more than one CEMS is used to measure the emissions from one affected source, due to multiple breechings or outlets, for example, the owner or operator shall report the results as required for each CEMS.

(b) *Reporting results of continuous monitoring system performance evaluations.* 1. The owner or operator of an affected source required to install a continuous monitoring system by a relevant standard shall furnish the department a copy of a written report of the results of the continuous monitoring system performance evaluation, as required under s. NR 460.07 (5), simultaneously with the results of the performance test required under s. NR 460.06, unless otherwise specified in the relevant standard.

2. The owner or operator of an affected source using a continuous opacity monitoring system to determine opacity compliance during any performance test required under s. NR 460.06 shall furnish the department 2 or, upon request, 3 copies of a written report of the results of the continuous opacity monitoring system performance evaluation conducted under s. NR 460.07 (5). The copies shall be furnished at least 15 calendar days before the performance test required under s. NR 460.06 is conducted.

(c) *Excess emissions and continuous monitoring system performance report and summary report.* 1. Excess emissions and parameter monitoring exceedances are defined in relevant standards. The owner or operator of an affected source required to install a continuous monitoring system by a relevant standard shall submit an excess emissions and continuous monitoring system performance report or a summary report or both to the department semiannually, except when any of the following occur:

a. More frequent reporting is specifically required by a relevant standard.

b. The department determines on a case-by-case basis that more frequent reporting is necessary to accurately assess the compliance status of the source.

c. The continuous monitoring system data are to be used directly for compliance determination and the source experienced excess emissions, in which case quarterly reports shall be submitted. Once a source reports excess emissions, the source shall follow a quarterly reporting format until a request to reduce reporting frequency under subd. 2. is approved.

2. Notwithstanding the frequency of reporting requirements specified in subd. 1., an owner or operator who is required by a relevant standard to submit excess emissions and continuous monitoring system performance and summary reports on a quarterly or more frequent basis may reduce the frequency of reporting for that standard to semiannual if all of the following conditions are met:

a. For 1 full year, the affected source's excess emissions and continuous monitoring system performance reports, which may be quarterly or monthly, continually demonstrate that the source is in compliance with the relevant standard.

b. The owner or operator continues to comply with all record-keeping and monitoring requirements specified in this chapter and the relevant standard.

c. The department does not object to a reduced frequency of reporting for the affected source, as provided in subd. 3.

3. The frequency of reporting of excess emissions and continuous monitoring system performance and summary reports required to comply with a relevant standard may be reduced only after the owner or operator notifies the department in writing of his or her intention to make a change and the department does not object to the intended change. In deciding whether to approve a reduced frequency of reporting, the department may review information concerning the source's entire previous performance his-

tory during the 5-year recordkeeping period prior to the intended change, including performance test results, monitoring data, and evaluations of an owner or operator's conformance with operation and maintenance requirements. The information may be used by the department to make a judgment about the source's potential for noncompliance in the future. If the department disapproves the owner or operator's request to reduce the frequency of reporting, the department shall notify the owner or operator in writing within 45 days after receiving notice of the owner or operator's intention. The notification from the department to the owner or operator shall specify the grounds on which the disapproval is based. In the absence of a notice of disapproval within 45 days, approval is automatically granted.

4. As soon as continuous monitoring system data indicate that the source is not in compliance with any emission limitation or operating parameter specified in the relevant standard, the frequency of reporting shall revert to the frequency specified in the relevant standard, and the owner or operator shall submit an excess emissions and continuous monitoring system performance report and summary report for the noncomplying emission points at the next appropriate reporting period following the noncomplying event. After demonstrating ongoing compliance with the relevant standard for another full year, the owner or operator may again request approval from the department to reduce the frequency of reporting for that standard, as provided for in subds. 2. and 3.

5. All excess emissions and monitoring system performance reports and all summary reports, if required, shall be delivered or postmarked by the 30th day following the end of each calendar half or quarter, as appropriate. Written reports of excess emissions or exceedances of process or control system parameters shall include all the information required in sub. (3) (a) 2. to 8., in s. NR 460.07 (3) (g) and (h), and in the relevant standard, and they shall contain the name, title and signature of the responsible official who is certifying the accuracy of the report. When no excess emissions or exceedances of a parameter have occurred, or a continuous monitoring system has not been inoperative, out of control, repaired or adjusted, this information shall be stated in the report.

6. As required under subds. 7. and 8., one summary report shall be submitted for the hazardous air pollutants monitored at each affected source, unless the relevant standard specifies that more than one summary report is required, such as one summary report for each hazardous air pollutant monitored. The summary report shall be entitled "Summary Report – Gaseous and Opacity Excess Emission and Continuous Monitoring System Performance" and shall contain all of the following information:

a. The company name and address of the affected source.

b. An identification of each hazardous air pollutant monitored at the affected source.

c. The beginning and ending dates of the reporting period.

d. A brief description of the process units.

e. The emission and operating parameter limitations specified in the relevant standards.

f. The monitoring equipment manufacturers and model numbers.

g. The date of the latest continuous monitoring system certification or audit.

h. The total operating time of the affected source during the reporting period.

i. An emission data summary, or similar summary if the owner or operator monitors control system parameters, including the total duration of excess emissions during the reporting period, recorded in minutes for opacity and hours for gases, the total duration of excess emissions expressed as a percent of the total source operating time during that reporting period, and a breakdown of the total duration of excess emissions during the reporting period into those that are due to startup or shutdown, control equipment

problems, process problems, other known causes, and other unknown causes.

j. A continuous monitoring system performance summary, or similar summary if the owner or operator monitors control system parameters, including the total continuous monitoring system downtime during the reporting period, recorded in minutes for opacity and hours for gases, the total duration of continuous monitoring system downtime expressed as a percent of the total source operating time during that reporting period, and a breakdown of the total continuous monitoring system downtime during the reporting period into periods that are due to monitoring equipment malfunctions, nonmonitoring equipment malfunctions, quality assurance/quality control calibrations, other known causes, and other unknown causes.

k. A description of any changes in continuous monitoring system, processes or controls since the last reporting period.

L. The name, title and signature of the responsible official who is certifying the accuracy of the report.

m. The date of the report.

7. If the total duration of excess emissions or process or control system parameter exceedances for the reporting period is less than one percent of the total operating time for the reporting period, and continuous monitoring system downtime for the reporting period is less than 5% of the total operating time for the reporting period, only the summary report shall be submitted, and the full excess emissions and continuous monitoring system performance report need not be submitted unless required by the department.

8. If the total duration of excess emissions or process or control system parameter exceedances for the reporting period is one percent or greater of the total operating time for the reporting period, or the total continuous monitoring system downtime for the reporting period is 5% or greater of the total operating time for the reporting period, both the summary report and the excess emissions and continuous monitoring system performance report shall be submitted.

(d) *Reporting continuous opacity monitoring system data produced during a performance test.* The owner or operator of an affected source required to use a continuous opacity monitoring system shall record the monitoring data produced during a performance test required under s. NR 460.06 and shall furnish the department a written report of the monitoring results. The report of continuous opacity monitoring system data shall be submitted simultaneously with the report of the performance test results required in sub. (4) (b).

**(6) WAIVER OF RECORDKEEPING OR REPORTING REQUIREMENTS.**

(a) Until a waiver of a recordkeeping or reporting requirement has been granted by the department under this subsection, the owner or operator of an affected source remains subject to the requirements of this section.

(b) Recordkeeping or reporting requirements may be waived upon written application to the department if, in the department's judgment, the affected source is achieving the relevant standards, or the source is operating under a compliance date extension, or the owner or operator has requested a compliance date extension and the department is still considering that request.

(c) If an application for a waiver of recordkeeping or reporting is made, the application shall accompany the request for a compliance date extension under s. NR 460.05 (7), any required compliance progress report or compliance status report required under 40 CFR part 63 or chs. NR 460 to 469 or in the source's part 70 permit, or an excess emissions and continuous monitoring system performance report required under sub. (5), whichever is applicable. The application shall include whatever information the owner or operator considers useful to convince the department that a waiver of recordkeeping or reporting is warranted.

(d) The department shall approve or deny a request for a waiver of recordkeeping or reporting requirements under this subsection when it does whichever of the following is applicable:

1. Approves or denies a compliance date extension.

2. Makes a determination of compliance following the submission of a required compliance status report or excess emissions and continuous monitoring systems performance report.

3. Makes a determination of suitable progress towards compliance following the submission of a compliance progress report.

(e) A waiver of any recordkeeping or reporting requirement granted under this subsection may be conditioned on other recordkeeping or reporting requirements deemed necessary by the department.

(f) Approval of any waiver granted under this section will not abrogate the department's authority or in any way prohibit the department from later canceling the waiver. The cancellation will be made only after notice is given to the owner or operator of the affected source.

**History:** Cr. Register, March, 1997, No. 495, eff. 4-1-97.

**NR 460.10 Control device requirements. (1) APPLICABILITY.** This section contains requirements for control devices used to comply with provisions in relevant standards. These requirements apply only to affected sources covered by relevant standards referring directly or indirectly to this section or to 40 CFR 63.11.

**(2) FLARES.** (a) Owners or operators using flares to comply with the provisions of 40 CFR part 63 or chs. NR 460 to 469 shall monitor these control devices to assure that they are operated and maintained in conformance with their designs. Applicable subparts of 40 CFR part 63 or applicable parts of chs. NR 460 to 469 will provide provisions stating how owners or operators using flares shall monitor these control devices.

(b) Flares shall be steam-assisted, air-assisted or non-assisted.

(c) Flares shall be operated at all times when emissions may be vented to them.

(d) Flares shall be designed for and operated with no visible emissions, except for periods not to exceed a total of 5 minutes during any 2 consecutive hours. Method 22 in Appendix A of 40 CFR part 60, incorporated by reference in s. NR 484.04, shall be used to determine the compliance of flares with the visible emission provisions of 40 CFR part 63 or chs. NR 460 to 469. The observation period is 2 hours and shall be used according to Method 22.

(e) Flares shall be operated with a flame present at all times. The presence of a flare pilot flame shall be monitored using a thermocouple or any other equivalent device to detect the presence of a flame.

(f) Flares shall be used only with the net heating value of the gas being combusted at 11.2 MJ/scm (300 Btu/scf) or greater if the flare is steam-assisted or air-assisted; or with the net heating value of the gas being combusted at 7.45 MJ/scm (200 Btu/scf) or greater if the flare is non-assisted. The net heating value of the gas being combusted in a flare shall be calculated using the following equation:

$$H_T = K \sum_{i=1}^n C_i H_i$$

where:

$H_T$  is the net heating value of the sample, MJ/scm; where the net enthalpy per mole of offgas is based on combustion at 25°C and 760 mm Hg, but the standard temperature for determining the volume corresponding to one mole is 20°C

K is a constant

$$1.740 \times 10^{-7} \left( \frac{1}{\text{ppmv}} \right) \left( \frac{\text{g-mole}}{\text{scm}} \right) \left( \frac{\text{MJ}}{\text{kcal}} \right)$$

where the standard temperature for (g-mole/scm) is 20°C

$C_i$  is the concentration of sample component i in ppmv on a wet basis, as measured for organics by Method 18 in Appendix A of 40 CFR part 60, incorporated by reference in s. NR 484.04, and measured for hydrogen and carbon monoxide by ASTM D1946-90, incorporated by reference in s. NR 484.10

$H_i$  is the net heat of combustion of sample component i, kcal/g-mole at 25°C and 760 mm Hg. The heats of combustion may be determined using ASTM D4809-95, incorporated by reference in s. NR 484.10, if published values are not available or cannot be calculated.

n is the number of sample components

(g) 1. Steam-assisted and nonassisted flares shall be designed for and operated with an exit velocity less than 18.3 m/sec (60 ft/sec), except as provided in subds. 2. and 3. The actual exit velocity of a flare shall be determined by dividing the volumetric flow rate of gas being combusted, in units of emission standard temperature and pressure, as determined by Method 2, 2A, 2C, or 2D in Appendix A of 40 CFR part 60, incorporated by reference in s. NR 484.04, as appropriate, by the unobstructed (free) cross-sectional area of the flare tip.

2. Steam-assisted and nonassisted flares designed for and operated with an exit velocity, as determined by the method specified in subd. 1., equal to or greater than 18.3 m/sec (60 ft/sec) but

less than 122 m/sec (400 ft/sec), are allowed if the net heating value of the gas being combusted is greater than 37.3 MJ/scm (1,000 Btu/scf).

3. Steam-assisted and nonassisted flares designed for and operated with an exit velocity, as determined by the method specified in subd. 1., less than the velocity  $V_{\text{max}}$ , as determined by the method specified in this subdivision, but less than 122 m/sec (400 ft/sec) are allowed. The maximum permitted velocity,  $V_{\text{max}}$ , for flares complying with this subdivision shall be determined by the following equation:

$$\text{Log}_{10}(V_{\text{max}}) = (H_T + 28.8)/31.7$$

where:

$V_{\text{max}}$  is the maximum permitted velocity, m/sec

28.8 is a constant

31.7 is a constant

$H_T$  is the net heating value as determined in par. (f)

(h) Air-assisted flares shall be designed and operated with an exit velocity less than the velocity  $V_{\text{max}}$ . The maximum permitted velocity,  $V_{\text{max}}$ , for air-assisted flares shall be determined by the following equation:

$$V_{\text{max}} = 8.706 + 0.7084(H_T)$$

where:

$V_{\text{max}}$  is the maximum permitted velocity, m/sec

8.706 is a constant

0.7084 is a constant

$H_T$  is the net heating value as determined in par. (f)

**History:** Cr. Register, March, 1997, No. 495, eff. 4-1-97; am. (2) (f), Register, November, 1999, No. 527, eff. 12-1-99.